

ECA2580



**SLOTTED TRUNKING WITH COVER A
8/12/8 DIM. 25X80**




IMMAGINE RAPPRESENTATIVA EC REPRESENTATIVE IMAGE

Trunkings > Panelboards systems > Cable management > Slotted trunkings > Slotted cable trunking > Grey - type a - wide slots 8/12/8

Technical Symbols/Marks/Approvals



Norms

EN 50085-1 EN 50085-2-3 UL 1565

Description

Slotted trunking made of self-extinguishing PVC-based technopolymer (UL94 - V0). Perforated bottom according to the Standard DIN 43659. Second break line at the base of the slots permits to remove the whole trunking wall (with tool).

Etim

GROUP EG000007 - Slotted cable trunking system

CLASS EC000012 - Slotted cable trunking system

Material	Polyvinyl chloride (PVC)	Halogen free	No	Colour	Grey
Type of fastening	Bottom perforation	Width	25 mm	Height	80 mm
Length	2 m	Distance of slots	12 mm	Slit width	8 mm
Type of side wall	Hole-/slot punching	Self-extinguishing	Yes	Flexible	No
Usable cross section	1520 mm ²	With cover	Yes	RAL-number	7030

Technical Characteristics

Separator predisposition NO

Documentation available for download



Certification
Certificato UL A-S
ATL AMF
E331386.pdf




Certification
RINA
DCMTVL_1005538
_380865962_2025.
PDF



Certification
Canali asolati tipo A
IMQ_EA850_2020.
pdf

Barcode



8050880885435
Cardboard
56 MT
0.26x0.18x2.027 [m]
24.9984 [kg]



8055035960920
Pallet
1008 MT
1.2x0.8x2.2 [m]
449.9712 [kg]