

**ECA60100**



**SLOTTED TRUNKING WITH COVER A  
8/12/8 DIM. 60X100**

Trunkings > Panelboards systems > Cable management >  
Slotted trunkings > Slotted cable trunking > Grey - type a - wide  
slots 8/12/8




IMMAGINE RAPPRESENTATIVA EC REPRESENTATIVE IMAGE

**Technical Symbols/Marks/Approvals**



**Norms**

EN 50085-1 EN 50085-2-3 UL 1565

**Description**

Slotted trunking made of self-extinguishing PVC-based technopolymer (UL94 - V0). Perforated bottom according to the Standard DIN 43659. Second break line at the base of the slots permits to remove the whole trunking wall (with tool).

**Etim**

**GROUP EG000007 - Slotted cable trunking system**

**CLASS EC000012 - Slotted cable trunking system**

<b>Material</b>	Polyvinyl chloride (PVC)	<b>Halogen free</b>	No	<b>Colour</b>	Grey
<b>Type of fastening</b>	Bottom perforation	<b>Width</b>	60 mm	<b>Height</b>	100 mm
<b>Length</b>	2 m	<b>Distance of slots</b>	12 mm	<b>Slit width</b>	8 mm
<b>Type of side wall</b>	Hole-/slot punching	<b>Self-extinguishing</b>	Yes	<b>Flexible</b>	No
<b>Usable cross section</b>	5332 mm <sup>2</sup>	<b>With cover</b>	Yes	<b>RAL-number</b>	7030

**Technical Characteristics**

**Separator predisposition** NO

## Documentation available for download



### Certification

Certificato UL A-S  
ATL AMF  
E331386.pdf



### Certification

RINA  
DCMTVL\_1005538  
\_380865962\_2025.  
PDF



### Certification

Canali asolati tipo A  
IMQ\_EA850\_2020.  
pdf

## Barcode



8050880885497

### Cardboard

24 MT

0.26x0.26x2.03 [m]

19.5 [kg]



8055035961071

### Pallet

288 MT

1.2x0.8x2.2 [m]

234 [kg]