elettrocanali
THE ITALIAN EVOLUTION OF ELECTRICITY

TECHNICAL DATA SHEET



ECAE12080B

EXTERNAL ANGLE DIM. 120X80 WHITE

Trunkings > Wall and ceiling > Solid cable trunkings > Series cp - fittings > Outer corner for cable trunkings

Technical Symbols/Marks/Approvals

IP40 | IK07 | GWT 650° | CE | RoHS II | MADE IN ITALY

Norms

EN 50085-1 EN50085-2-1

Description

External angle for 90° direction change. Snap-on connection to the duct.

Etim

GROUP EG000006 - Installation ducts for wall and ceiling

CLASS EC000872 - Outer corner for wall duct

Degree of protection (IP)	IP40	**Material**	Plastic	**Material quality**	Acrylonitrile butadiene styrene (ABS)
Halogen free	Yes	**Anti-bacterial treatment**	No	**Surface protection**	Untreated
Colour	White	**Impact strength**	IK07	**Width**	120 mm
Depth	80 mm	**Model**	Moulded hood	**RAL-number**	9001
Mounting method cover	Spanned	**With protective foil**	No	**Working temperature**	-5 ÷ 60 °C
With cable fixing clip	No	**With duct connector**	Yes	**Bottom perforation**	No
Angle	90 ÷ 90 °	**Number of covers**	1	**Cover width 1**	120 mm
Cover width 2	0 mm	**Cover width 3**	0 mm	**Symmetric**	Yes

Documentation available for download



Certification

Canali CPH IMQ_CA02.06517_2020.pdf



Certification

Canali e Minic Serie MC-CP.pdf



Certification

LICENCE 669941_CP-MC.pdf

Information, dimensions, diagrams and images are provided for informational purposes only and are current as of the date indicated. These elements may be subject to change at any time.

Barcode

8050880885626

Cardboard

10 NR

0.25x0.33x0.105 [m]

1 [kg]

Information, dimensions, diagrams and images are provided for informational purposes only and are current as of the date indicated. These elements may be subject to change at any time.