elettrocanali
THE ITALIAN EVOLUTION OF ELECTRICITY

TECHNICAL DATA SHEET



ECAI6040B

INTERNAL ANGLE DIM. 60X40 WHITE

Trunkings > Wall and ceiling > Solid cable trunkings > Series cp - fittings > Inner corner for cable trunkings

Technical Symbols/Marks/Approvals

IP40 | IK07 | GWT 650° | CE | RoHS II | MADE IN ITALY

Norms

EN 50085-1 EN50085-2-1

Description

Internal angle for 90° direction change. Snap-on connection to the duct.

Etim

GROUP EG000006 - Installation ducts for wall and ceiling

CLASS EC000867 - Inner corner for wall duct

Degree of protection (IP)	IP40	**Material**	Plastic	**Material quality**	Acrylonitrile butadiene styrene (ABS)
Halogen free	Yes	**Anti-bacterial treatment**	No	**Surface protection**	Untreated
Colour	White	**Impact strength**	IK07	**Width**	60 mm
Depth	40 mm	**Model**	Moulded hood	**RAL-number**	9001
Mounting method cover	Spanned	**With protective foil**	No	**Working temperature**	-5-60 °C
With cable fixing clip	No	**With duct connector**	Yes	**Shape**	Symmetric
Bottom perforation	No	**Angle**	90-90 °	**Number of covers**	1
Cover width 1	60 mm	**Cover width 2**	0 mm	**Cover width 3**	0 mm

Documentation available for download



Certification

Canali CPH IMQ_CA02.06517_2020.pdf



Certification

Canali e Minic Serie MC-CP.pdf



Certification

LICENCE 669941_CP-MC.pdf

Information, dimensions, diagrams and images are provided for informational purposes only and are current as of the date indicated. These elements may be subject to change at any time.

Barcode

8050880886241

Pack

2 NR

0.056 [kg]

8057711592838

Cardboard

50 NR

0.39x0.295x0.15 [m]

1.4 [kg]

Information, dimensions, diagrams and images are provided for informational purposes only and are current as of the date indicated. These elements may be subject to change at any time.