
elettrocanali
THE ITALIAN EVOLUTION OF ELECTRICITY

TECHNICAL DATA SHEET



ECAP2010B

FLAT ANGLE DIM. 20X10 WHITE

Trunkings > Wall and ceiling > Miniature solid trunkings > Series mc-mca-ma - fittings > Flat corner for mini trunkings

Technical Symbols/Marks/Approvals

IP40 | IK07 | GWT 650° | CE | RoHS II | NF | MADE IN ITALY

Norms

EN 50085-1 EN50085-2-1

Description

Flat angle for 90° direction changes. Snap-on connection to the mini-trunking.

Etim

GROUP EG000006 - Installation ducts for wall and ceiling

CLASS EC000876 - Flat bend for wall duct

Degree of protection (IP)	IP40	**Material**	Plastic	**Material quality**	Acrylonitrile butadiene styrene (ABS)
Halogen free	Yes	**Anti-bacterial treatment**	No	**Surface protection**	Untreated
Colour	White	**Impact strength**	IK07	**Width**	20 mm
Depth	10 mm	**Model**	Moulded hood	**RAL-number**	9001
Mounting method cover	Spanned	**With protective foil**	No	**Working temperature**	-5 ÷ 60 °C
With cable fixing clip	No	**With duct connector**	No	**Bottom perforation**	No
Angle	90 ÷ 90 °	**Number of covers**	1	**Cover width 1**	20 mm
Cover width 2	0 mm	**Cover width 3**	0 mm	**Symmetric**	Yes
Direction	Rising/descending				

Documentation available for download



Certification

Canali e Minic Serie MC-CP.pdf



Certification

Minicanali Serie MCA.pdf



Certification

LICENCE 669941_CP-MC.pdf

Information, dimensions, diagrams and images are provided for informational purposes only and are current as of the date indicated. These elements may be subject to change at any time.

Barcode

8050880886395

Pack

2 NR

0.012 [kg]

8057711592852

Cardboard

50 NR

0.165x0.175x0.105 [m]

0.3 [kg]

Information, dimensions, diagrams and images are provided for informational purposes only and are current as of the date indicated. These elements may be subject to change at any time.