elettrocanali
THE ITALIAN EVOLUTION OF ELECTRICITY

TECHNICAL DATA SHEET



IMMAGINE RAPPRESENTATIVA — REPRESENTATIVE IMAGE

ECCAP5012B

FLOOR CABLE TRUNKING WITH COVER mm 50X12 WHITE - 3 COMPARTMENTS

Trunkings > Wall and ceiling > Solid cable trunkings > Series cap - floor trunkings > Floor mount trunkings

Technical Symbols/Marks/Approvals

IP40 | IK08 | UL94 V0 | GWT 960° | RoHS II | CE | MADE IN ITALY

Norms

EN 50085-1 EN 50085-2-1

Description

Floor trunking made of self-extinguishing rigid PVC technopolymer. Impact resistance: 6J. Base designed for silicone adhesive fixing and perforated for screw and plug fixing. Wrap-around cover, removable only with tools. Trampling-resistant, load capacity 0.4 kg/cm².

Etim

GROUP EG000006 - Installation ducts for wall and ceiling

CLASS EC000722 - On-floor installation duct

Degree of protection (IP)	IP40	**Material**	Plastic	**Material quality**	Other
Halogen free	No	**Anti-bacterial treatment**	No	**Colour**	White
Impact strength	IK07	**Width**	50 mm	**Height**	12 mm
Length	2000 mm	**RAL-number**	9001	**Working temperature**	-5 ÷ 60 °C
Number of channels	3	**With cover cap**	No	**Permitted cable diameter**	6 ÷ 10 mm
Bottom perforation	Yes	**Slotted hole**	Yes	**With fixation**	No
Demountable	Yes	**Self-adhesive**	No	**Sealing lip**	Yes
With anti-slip layer	No	**Reflective**	No	**Fuel- and oil resistant**	No
Resistance to vertical load applied in a small surface according IEC 61084-2-2	1000 N	**Resistance to vertical load applied in a large surface according IEC 61084-2-2**	7000 N	**Suitable for car**	No
Suitable for truck	No	**Bending strength**	Rigid		

Information, dimensions, diagrams and images are provided for informational purposes only and are current as of the date indicated. These elements may be subject to change at any time.

Barcode

8050880886746

Cardboard

50 MT

0.195x0.102x2.025 [m]

13.5 [kg]

Information, dimensions, diagrams and images are provided for informational purposes only and are current as of the date indicated. These elements may be subject to change at any time.