elettrocanali
THE ITALIAN EVOLUTION OF ELECTRICITY

**TECHNICAL DATA SHEET**




# ECCF20

## SNAP CONDUIT CLIP Ø20 mm - GREY

Conduits and fittings > Accessories and fittings > Fixings > Conduits fixing accessories > Conduit clips > Snap conduit clips

### Technical Symbols/Marks/Approvals

HF | GWT 650° | UL94 V2 | CE | RoHS II | MADE IN ITALY

### Norms

EN 61386-1 EN 61386-21 EN 61386-22

## Description

Snap-in conduit clip made of impact-resistant ABS-based technopolymer, Halogen Free according to EN 60754-1, EN 60754-2, and EN 60754-3 standards. Resistance to abnormal heat: up to 650 °C (GWT IEC 60695-2-11 standard). Slotted base to facilitate installation alignment. Lateral coupling for combined installation and on GC rails. Manufactured in compliance with EN 61386-1 standards where applicable.
Diameter 20 mm

## Etim

### GROUP EG000010 - Installation material for cables and tubes

### CLASS EC000368 - Tube clamp

| | | | | | |
|---|---|---|---|---|---|
| **Material** | Plastic | **Material quality** | Acrylonitrile butadiene styrene (ABS) | **Halogen free** | Yes |
| **Surface protection** | Other | **Colour** | Grey | **Type of fastening** | Screw hole |
| **Working temperature** | -25 ÷ 70 °C | **Suitable for pipe diameter** | 20 ÷ 20 mm | **Closed** | No |
| **Suitable for protective hoses** | Yes | **Connectable** | Yes | **Max. number of tubes** | 1 |
| **With inlay** | No | **With wall gasket** | No | | |



Information, dimensions, diagrams and images are provided for informational purposes only and are current as of the date indicated. These elements may be subject to change at any time.

## Barcode



8054320283041

**Pack**

100 NR

0.4 [kg]



8059307210423

**Cardboard**

1000 NR

0.39x0.295x0.15 [m]

4 [kg]



Information, dimensions, diagrams and images are provided for informational purposes only and are current as of the date indicated. These elements may be subject to change at any time.