

**ECCF25**



**SNAP CONDUIT CLIP Ø25 mm - GREY**

Conduits and fittings > Accessories and fittings > Fixings > Conduits fixing accessories > Conduit clips > Snap conduit clips



**Technical Symbols/Marks/Approvals**

<b>HF</b>	<b>GWT 650°</b>	<b>UL94 V2</b>	<b>CE</b>	<b>RoHS II</b>	<b>MADE IN ITALY</b>
-----------	-----------------	----------------	-----------	----------------	----------------------

**Norms**

EN 61386-1 EN 61386-21 EN 61386-22

**Description**

Snap-in conduit clip made of impact-resistant ABS-based technopolymer, Halogen Free according to EN 60754-1, EN 60754-2, and EN 60754-3 standards. Resistance to abnormal heat: up to 650 °C (GWT IEC 60695-2-11 standard). Slotted base to facilitate installation alignment. Lateral coupling for combined installation and on GC rails. Manufactured in compliance with EN 61386-1 standards where applicable.  
Diameter 25 mm

**Etim**

**GROUP EG000010 - Installation material for cables and tubes**

**CLASS EC000368 - Tube clamp**

<b>Material</b>	Plastic	<b>Material quality</b>	Acrylonitrile butadiene styrene (ABS)	<b>Halogen free</b>	Yes
<b>Surface protection</b>	Other	<b>Colour</b>	Grey	<b>Type of fastening</b>	Screw hole
<b>Working temperature</b>	-25-70 °C	<b>Suitable for pipe diameter</b>	25-25 mm	<b>Closed</b>	No
<b>Suitable for protective hoses</b>	Yes	<b>Connectable</b>	Yes	<b>Max. number of tubes</b>	1
<b>With inlay</b>	No	<b>With wall gasket</b>	No		

## Barcode



8054320283027

**Pack**

100 NR

0.47 [kg]



8059307210447

**Cardboard**

1000 NR

0.39x0.295x0.21 [m]

4.7 [kg]