elettrocanali
THE ITALIAN EVOLUTION OF ELECTRICITY

TECHNICAL DATA SHEET



ECCF50

SNAP CONDUIT CLIP Ø50 mm - GREY

Conduits and fittings > Accessories and fittings > Fixings > Conduits fixing accessories > Conduit clips > Snap conduit clips

Technical Symbols/Marks/Approvals

HF | GWT 650° | UL94 V2 | CE | RoHS II | MADE IN ITALY

Norms

EN 61386-1 EN 61386-21 EN 61386-22

Description

Snap-in conduit clip made of impact-resistant ABS-based technopolymer, Halogen Free according to EN 60754-1, EN 60754-2, and EN 60754-3 standards. Resistance to abnormal heat: up to 650 °C (GWT IEC 60695-2-11 standard). Slotted base to facilitate installation alignment. Lateral coupling for combined installation and on GC rails. Manufactured in compliance with EN 61386-1 standards where applicable.
Diameter 50 mm

Etim

GROUP EG000010 - Installation material for cables and tubes

CLASS EC000368 - Tube clamp

Material	Plastic	**Material quality**	Acrylonitrile butadiene styrene (ABS)	**Halogen free**	Yes
Surface protection	Other	**Colour**	Grey	**Type of fastening**	Screw hole
Working temperature	-25 ÷ 70 °C	**Suitable for pipe diameter**	50 ÷ 50 mm	**Closed**	No
Suitable for protective hoses	Yes	**Connectable**	Yes	**Max. number of tubes**	1
With inlay	No	**With wall gasket**	No		

Information, dimensions, diagrams and images are provided for informational purposes only and are current as of the date indicated. These elements may be subject to change at any time.

Barcode

8050880886791

Pack

25 NR

0.42 [kg]

8057711593101

Cardboard

250 NR

0.39x0.295x0.21 [m]

4.2 [kg]

Information, dimensions, diagrams and images are provided for informational purposes only and are current as of the date indicated. These elements may be subject to change at any time.