elettrocanali
THE ITALIAN EVOLUTION OF ELECTRICITY

TECHNICAL DATA SHEET



ECCFF1

TIE CLIP Ø16-32 mm - GREY

Conduits and fittings > Accessories and fittings > Fixings > Conduits fixing accessories > Cable tie

Technical Symbols/Marks/Approvals

HF | GWT 650° | UL94 V2 | CE | RoHS II | MADE IN ITALY

Norms

EN 61386-1 EN 61386-21 EN 61386-22

Description

Adjustable conduit tie clip made of impact-resistant polyamide-based technopolymer, Halogen Free according to EN 60754-1, EN 60754-2, and EN 60754-3 standards. Resistance to abnormal heat: up to 650 °C (GWT IEC 60695-2-11 standard). Slotted base to facilitate installation alignment. Tensile strength 100 N. Manufactured in compliance with EN 61386-1 standards where applicable. Minimum diameter 16 mm - maximum 32 mm

Etim

GROUP EG000049 - Fasteners

CLASS EC000046 - Cable tie

Material	Plastic	**Material quality**	Polyamide (PA)	**Halogen free**	Yes
Surface protection	Untreated	**Colour**	Grey	**Transparent**	No
Type of fastening	Screw hole	**Model**	Internal toothing	**Band width**	7.5 mm
Length belt/tape/tie	110 mm	**Tie thickness**	1.6 mm	**Bundle diameter**	16 ÷ 32 mm
Min. tensile strength	100 N	**Operating temperature**	-25 ÷ 70 °C	**Mounting temperature**	-5 ÷ 60 °C
Band closure	Plastic lip/-cam	**UV-stable according to ASTM D6779**	No	**Fluorescent**	No
Detectable	No	**Text strip**	None	**Releasable closure**	No
VG approval	No	**MIL approval**	No	**UL approval**	No
Inflammability class of insulation material according to UL94	V2				

Information, dimensions, diagrams and images are provided for informational purposes only and are current as of the date indicated. These elements may be subject to change at any time.

Barcode

8050880886869

Pack

100 NR

0.43 [kg]

8057711593170

Cardboard

1400 NR

0.39x0.295x0.3 [m]

6.02 [kg]

Information, dimensions, diagrams and images are provided for informational purposes only and are current as of the date indicated. These elements may be subject to change at any time.