

**ECCFF1**



**TIE CLIP Ø16-32 mm - GREY**

Conduits and fittings > Accessories and fittings > Fixings > Conduits fixing accessories > Cable tie > Cable tie



**Technical Symbols/Marks/Approvals**

HF	GWT 650°	UL94 V2	CE	RoHS II	MADE IN ITALY
----	-------------	------------	----	---------	---------------------

**Norms**

EN 61386-1 EN 61386-21 EN 61386-22

**Description**

Adjustable conduit tie clip made of impact-resistant polyamide-based technopolymer, Halogen Free according to EN 60754-1, EN 60754-2, and EN 60754-3 standards. Resistance to abnormal heat: up to 650 °C (GWT IEC 60695-2-11 standard). Slotted base to facilitate installation alignment. Tensile strength 100 N. Manufactured in compliance with EN 61386-1 standards where applicable. Minimum diameter 16 mm - maximum 32 mm

**Etim**

**GROUP EG000049 - Fasteners**

**CLASS EC000046 - Cable tie**

<b>Material</b>	Plastic	<b>Material quality</b>	Polyamide (PA)	<b>Halogen free</b>	Yes
<b>Surface protection</b>	Untreated	<b>Colour</b>	Grey	<b>Transparent</b>	No
<b>Type of fastening</b>	Screw hole	<b>Model</b>	Internal toothing	<b>Band width</b>	7.5 mm
<b>Length belt/tape/tie</b>	110 mm	<b>Tie thickness</b>	1.6 mm	<b>Bundle diameter</b>	16-32 mm
<b>Min. tensile strength</b>	100 N	<b>Operating temperature</b>	-25-70 °C	<b>Mounting temperature</b>	-5-60 °C
<b>Band closure</b>	Plastic lip/-cam	<b>UV-stable according to ASTM D6779</b>	No	<b>Fluorescent</b>	No
<b>Detectable</b>	No	<b>Text strip</b>	None	<b>Releasable closure</b>	No
<b>VG approval</b>	No	<b>MIL approval</b>	No	<b>UL approval</b>	No
<b>Inflammability class of insulation material according to UL94</b>	V2				

## Barcode



8050880886869

**Pack**

100 NR

0.43 [kg]



8057711593170

**Cardboard**

1400 NR

0.39x0.295x0.3 [m]

6.02 [kg]