

ECCFF2

TIE CLIP Ø32-63 mm - GREY

Conduits and fittings > Accessories and fittings > Fixings > Conduits fixing accessories > Cable tie > Cable tie



Technical Symbols/Marks/Approvals



Norms

EN 61386-1 EN 61386-21 EN 61386-22

Description

Adjustable conduit tie clip made of impact-resistant polyamide-based technopolymer, Halogen Free according to EN 60754-1, EN 60754-2, and EN 60754-3 standards. Resistance to abnormal heat: up to 650 °C (GWT IEC 60695-2-11 standard). Slotted base to facilitate installation alignment. Tensile strength 100 N. Manufactured in compliance with EN 61386-1 standards where applicable. Minimum diameter 32 mm - maximum 63 mm

Etim

GROUP EG000049 - Fasteners

CLASS EC000046 - Cable tie

Material	Plastic	Material quality	Polyamide (PA)	Halogen free	Yes
Surface protection	Untreated	Colour	Grey	Transparent	No
Type of fastening	Screw hole	Model	Internal toothing	Band width	8 mm
Length belt/tape/tie	190 mm	Tie thickness	1.6 mm	Bundle diameter	32-63 mm
Min. tensile strength	100 N	Operating temperature	-25-70 °C	Mounting temperature	-5-60 °C
Band closure	Plastic lip/-cam	UV-stable according to ASTM D6779	No	Fluorescent	No
Detectable	No	Text strip	None	Releasable closure	No
VG approval	No	MIL approval	No	UL approval	No
Inflammability class of insulation material according to UL94	V2				

Barcode



8050880886876

Pack

50 NR

0.415 [kg]



8057711593187

Cardboard

700 NR

0.39x0.295x0.3 [m]

5.81 [kg]