

ECCP12060B

CABLE TRUNKING WITH COVER DIM. 120X60 WHITE

Trunkings > Wall and ceiling > Solid cable trunkings > Series cp - trunking lengths > Cable trunkings > White



IMMAGINE RAPPRESENTATIVA **EC** REPRESENTATIVE IMAGE

Technical Symbols/Marks/Approvals



Norms

EN 50085-1 EN 50085-2-1

Description

Cable duct made of self-extinguishing rigid PVC technopolymer. The bottom is pre-drilled for fixing with screws and anchors. A front-hinged lid is included.

Etim

GROUP EG000006 - Installation ducts for wall and ceiling

CLASS EC001938 - Wall duct

Degree of protection (IP)	IP40	Material	Plastic	Material quality	Polyvinyl chloride (PVC)
Halogen free	No	Anti-bacterial treatment	No	Surface protection	Untreated
Colour	White	Impact strength	IK07	Width	120 mm
Depth	60 mm	Length	2 m	Usable cross section	6340 mm ²
RAL-number	9001	Mounting method cover	Spanned	With protective foil	No
Working temperature	-5-60 °C	Number of plug-in partitions	2	With cable fixing clip	No
With duct connector	No	Bottom perforation	No	Number of covers	1
Cover width 1	120 mm	Symmetric	Yes	Covers included	Yes
Construction type rectangular	Yes	Construction rear wall (inner side)	Perforated		

Documentation available for download

Instruction booklet
Istruzioni canali.pdf

Certification
Canali e Minic Serie MC-CP.pdf

Certification
LICENCE 669941_CP-MC.pdf

Barcode



8050880887231

Cardboard

20 MT

0.26x0.18x2.027 [m]

23.5 [kg]



8055035961606

Pallet

360 MT

1.2x0.8x2.2 [m]

423 [kg]