

## ECCP4080B

### CABLE TRUNKING WITH COVER DIM. 40X80 WHITE



Trunkings > Wall and ceiling > Solid cable trunkings > Series cp  
- trunking lengths > Cable trunkings > White



IMMAGINE RAPPRESENTATIVA EC REPRESENTATIVE IMAGE

#### Technical Symbols/Marks/Approvals



#### Norms

EN 50085-1 EN 50085-2-1

## Description

Cable duct made of self-extinguishing rigid PVC technopolymer. The bottom is pre-drilled for fixing with screws and anchors. A front-hinged lid is included.


## Etim

**GROUP EG000006 - Installation ducts for wall and ceiling**

**CLASS EC001938 - Wall duct**

<b>Degree of protection (IP)</b>	IP40	<b>Material</b>	Plastic	<b>Material quality</b>	Polyvinyl chloride (PVC)
<b>Halogen free</b>	No	<b>Anti-bacterial treatment</b>	No	<b>Surface protection</b>	Untreated
<b>Colour</b>	White	<b>Impact strength</b>	IK07	<b>Width</b>	40 mm
<b>Depth</b>	80 mm	<b>Length</b>	2 m	<b>Usable cross section</b>	2530 mm <sup>2</sup>
<b>RAL-number</b>	9001	<b>Mounting method cover</b>	Spanned	<b>With protective foil</b>	No
<b>Working temperature</b>	-5-60 °C	<b>Number of plug-in partitions</b>	0	<b>With cable fixing clip</b>	No
<b>With duct connector</b>	No	<b>Bottom perforation</b>	No	<b>Number of covers</b>	1
<b>Cover width 1</b>	40 mm	<b>Symmetric</b>	Yes	<b>Covers included</b>	Yes
<b>Construction type rectangular</b>	Yes	<b>Construction rear wall (inner side)</b>	Perforated		

## Documentation available for download



**Instruction booklet**  
Istruzioni canali.pdf



**Certification**  
Canali e Minic Serie  
MC-CP.pdf



**Certification**  
LICENCE  
669941\_CP-MC.pdf

## Barcode



8050880887446

**Cardboard**

40 MT

0.26x0.18x2.027 [m]

27.5 [kg]



8055035961866

**Pallet**

720 MT

1.2x0.8x2.2 [m]

495 [kg]