

ECCRS16



BEND 90° IP40 Ø16 mm - GREY

Conduits and fittings > Accessories and fittings > Joints and fittings > Ip40-ip64 fittings > Coupler bend conduit - conduit > 90° bend



Technical Symbols/Marks/Approvals

IP40	UL94 V0	GWT 960°	IK07	CE	RoHS II		
MADE IN ITALY							

Norms

EN 61386-1 EN 61386-21

Description

90° bend for the connection between two pipes of identical diameter, made of shockproof technopolymer based on rigid PVC. IP40 protection rating. V0 self-extinguishing grade according to UL94 standard. Resistance to abnormal heat (GWT IEC 60695-2-11): up to 960 °C. Manufactured in compliance with EN 61386-1 and EN 61386-21 standards.
Diameter 16 mm - bending radius 54 mm


Etim

GROUP EG000002 - Pipes/hoses for cable installation


CLASS EC000936 - Bend for installation tubes

Material	Plastic	Material quality	Polyvinyl chloride (PVC)	Halogen free	No
Surface protection	Untreated	Colour	Grey	Model	Plug-in
Diameter	16 mm	Flexible	No	UV resistant	Yes
Quality of surface coating	Uncoated	Surface polished	No	Surface brushed	No
Compressive strength class according to EN 61386-1	None	Impact strength class according to EN 61386-1	Medium (class 3 / 2 Joule)	For nominal tube diameter	16 mm
With sleeve	Yes	Two-part	No	With inspection opening and cover	No
Radius	54 mm	Bend angle	90 °C		

Documentation available for download



Certification
Tubo Rigido TG15
e
Raccordi_2023.pdf



Certification
LICENCE NF -
TG15 -2022 -
Licence - Certificat
Produits-14694838-
778138-
0000732340-
6.p....pdf

Barcode



8050880888047
Pack
50 NR
0.6 [kg]



8053676578313
Cardboard
1000 NR
0.605x0.4x0.26 [m]
12 [kg]