

## ECCRS25H



### HF BEND 90° IP40 Ø25 mm - GREY

Conduits and fittings > Accessories and fittings > Joints and fittings > Ip40-ip64 fittings > Coupler bend conduit - conduit > 90° bend - halogen free



IMMAGINE RAPPRESENTATIVA  REPRESENTATIVE IMAGE

#### Technical Symbols/Marks/Approvals

IP40	HF	GWT 650°	IK07	CE	RoHS II	MADE IN ITALY
------	----	----------	------	----	---------	---------------

#### Norms

EN 61386-1 EN 61386-21

## Description

90° bend for the connection between two pipes of identical diameter, made of shockproof Halogen-Free ABS-based technopolymer. Resistance to abnormal heat (GWT IEC 60695-2-11): up to 650 °C. Manufactured in compliance with EN 61386-1 and EN 61386-21 standards.

Diameter 25 mm - bending radius 85 mm

## Etim

**GROUP EG000002 - Pipes/hoses for cable installation**

**CLASS EC000936 - Bend for installation tubes**

<b>Material</b>	Plastic	<b>Material quality</b>	Other	<b>Halogen free</b>	Yes
<b>Surface protection</b>	Untreated	<b>Colour</b>	Grey	<b>Model</b>	Plug-in
<b>Diameter</b>	25 mm	<b>Flexible</b>	No	<b>UV resistant</b>	Yes
<b>Quality of surface coating</b>	Uncoated	<b>Surface polished</b>	No	<b>Surface brushed</b>	No
<b>Compressive strength class according to EN 61386-1</b>	None	<b>Impact strength class according to EN 61386-1</b>	Medium (class 3 / 2 Joule)	<b>For nominal tube diameter</b>	25 mm
<b>With sleeve</b>	Yes	<b>Two-part</b>	No	<b>With inspection opening and cover</b>	No
<b>Radius</b>	85 mm	<b>Bend angle</b>	90 °C		

## Barcode



8050880888092

**Pack**

25 NR

0.5825 [kg]



8057711593491

**Cardboard**

300 NR

0.605x0.4x0.26 [m]

6.99 [kg]