

**ECCRS32**



**BEND 90° IP40 Ø32 mm - GREY**

Conduits and fittings > Accessories and fittings > Joints and fittings > Ip40-ip64 fittings > Coupler bend conduit - conduit > 90° bend



IMMAGINE RAPPRESENTATIVA **EC** REPRESENTATIVE IMAGE

**Technical Symbols/Marks/Approvals**

IP40	UL94 V0	GWT 960°	IK07	CE	RoHS II		
MADE IN ITALY							

**Norms**

EN 61386-1 EN 61386-21

**Description**

90° bend for the connection between two pipes of identical diameter, made of shockproof technopolymer based on rigid PVC. IP40 protection rating. V0 self-extinguishing grade according to UL94 standard. Resistance to abnormal heat (GWT IEC 60695-2-11): up to 960 °C. Manufactured in compliance with EN 61386-1 and EN 61386-21 standards. Diameter 32 mm - bending radius 110 mm

**Etim**

**GROUP EG000002 - Pipes/hoses for cable installation**


**CLASS EC000936 - Bend for installation tubes**

<b>Material</b>	Plastic	<b>Material quality</b>	Polyvinyl chloride (PVC)	<b>Halogen free</b>	No
<b>Surface protection</b>	Untreated	<b>Colour</b>	Grey	<b>Model</b>	Plug-in
<b>Diameter</b>	32 mm	<b>Flexible</b>	No	<b>UV resistant</b>	Yes
<b>Quality of surface coating</b>	Uncoated	<b>Surface polished</b>	No	<b>Surface brushed</b>	No
<b>Compressive strength class according to EN 61386-1</b>	None	<b>Impact strength class according to EN 61386-1</b>	Medium (class 3 / 2 Joule)	<b>For nominal tube diameter</b>	32 mm
<b>With sleeve</b>	Yes	<b>Two-part</b>	No	<b>With inspection opening and cover</b>	No
<b>Radius</b>	110 mm	<b>Bend angle</b>	90 °C		

## Documentation available for download



**Certification**  
Tubo Rigido TG15  
e  
Raccordi\_2023.pdf



**Certification**  
LICENCE NF -  
TG15 -2022 -  
Licence - Certificat  
Produits-14694838-  
778138-  
0000732340-  
6.p....pdf

## Barcode



8050880888108

**Cardboard**

100 NR

0.605x0.4x0.26 [m]

6.5 [kg]