elettrocanali
THE ITALIAN EVOLUTION OF ELECTRICITY

TECHNICAL DATA SHEET



ECCRS32H

HF BEND 90° IP40 Ø32 mm - GREY

Conduits and fittings > Accessories and fittings > Joints and fittings > Ip40-ip64 fittings > Coupler bend conduit - conduit > 90° bend - halogen free

Technical Symbols/Marks/Approvals

IP40 | HF | GWT 650° | IK07 | CE | RoHS II | MADE IN ITALY

Norms

EN 61386-1 EN 61386-21

Description

90° bend for the connection between two pipes of identical diameter, made of shockproof Halogen-Free ABS-based technopolymer. Resistance to abnormal heat (GWT IEC 60695-2-11): up to 650 °C. Manufactured in compliance with EN 61386-1 and EN 61386-21 standards.
Diameter 32 mm - bending radius 110 mm

Etim

GROUP EG000002 - Pipes/hoses for cable installation

CLASS EC000936 - Bend for installation tubes

Material	Plastic	**Material quality**	Other	**Halogen free**	Yes
Surface protection	Untreated	**Colour**	Grey	**Model**	Plug-in
Diameter	32 mm	**Flexible**	No	**UV resistant**	Yes
Quality of surface coating	Uncoated	**Surface polished**	No	**Surface brushed**	No
Compressive strength class according to EN 61386-1	None	**Impact strength class according to EN 61386-1**	Medium (class 3 / 2 Joule)	**Suitable for nominal tube diameter**	32 mm
With sleeve	Yes	**Two-part**	No	**With inspection opening and cover**	No
Radius	110 mm	**Bend angle**	90 °C		

Information, dimensions, diagrams and images are provided for informational purposes only and are current as of the date indicated. These elements may be subject to change at any time.

Barcode



8050880888115

Cardboard

100 NR

0.605x0.4x0.26 [m]

5 [kg]

Information, dimensions, diagrams and images are provided for informational purposes only and are current as of the date indicated. These elements may be subject to change at any time.