elettrocanali
THE ITALIAN EVOLUTION OF ELECTRICITY

TECHNICAL DATA SHEET



ECCRS40

BEND 90° IP40 Ø40 mm - GREY

Conduits and fittings > Accessories and fittings > Joints and fittings > Ip40-ip64 fittings > Coupler bend conduit - conduit > 90° bend

Technical Symbols/Marks/Approvals

IP40 | UL94 V0 | GWT 960° | IK07 | CE | RoHS II | NF | MADE IN ITALY

Norms

EN 61386-1 EN 61386-21

Description

90° bend for the connection between two pipes of identical diameter, made of shockproof technopolymer based on rigid PVC. IP40 protection rating. V0 self-extinguishing grade according to UL94 standard. Resistance to abnormal heat (GWT IEC 60695-2-11): up to 960 °C. Manufactured in compliance with EN 61386-1 and EN 61386-21 standards.
Diameter 40 mm - bending radius 138 mm

Etim

GROUP EG000002 - Pipes/hoses for cable installation

CLASS EC000936 - Bend for installation tubes

Material	Plastic	**Material quality**	Polyvinyl chloride (PVC)	**Halogen free**	No
Surface protection	Untreated	**Colour**	Grey	**Model**	Plug-in
Diameter	40 mm	**Flexible**	No	**UV resistant**	Yes
Quality of surface coating	Uncoated	**Surface polished**	No	**Surface brushed**	No
Compressive strength class according to EN 61386-1	None	**Impact strength class according to EN 61386-1**	Medium (class 3 / 2 Joule)	**Suitable for nominal tube diameter**	40 mm
With sleeve	Yes	**Two-part**	No	**With inspection opening and cover**	No
Radius	138 mm	**Bend angle**	90 °C		

Information, dimensions, diagrams and images are provided for informational purposes only and are current as of the date indicated. These elements may be subject to change at any time.

Documentation available for download



Certification

Tubo Rigido TG15 e Raccordi_2023.pdf



Certification

LICENCE NF - TG15 -2022 - Licence - Certificat Produits-14694838-778138-0000732340-6.p....pdf

Barcode

8050880888122

Cardboard

100 NR

0.605x0.4x0.36 [m]

10.5 [kg]

Information, dimensions, diagrams and images are provided for informational purposes only and are current as of the date indicated. These elements may be subject to change at any time.