

ECGFE22

FLEXIBLE SPIRAL CONDUIT 23114 Ø22 mm - 30 m - GREY

Conduits and fittings > Spiral conduits > Flexible spiral conduits > Series gfe - class 23114 - 320 n > Spiral flexible conduits



IMMAGINE RAPPRESENTATIVA REPRESENTATIVE IMAGE

Technical Symbols/Marks/Approvals



Norms

EN 61386-1 EN 61386-23 UL 1696

Etim

GROUP EG000003 - Protective hose systems

CLASS EC001177 - Protective plastic hose

Material	Polyvinyl chloride (PVC)	Halogen free	No	Colour	Grey
UV resistant	Yes	Working temperature	5-60 °C	Nominal diameter	20 mm
Inner diameter	22 mm	Outer diameter	27.7 mm	Compressive strength	320 N
Bending radius, static	220 mm	Tensile strength	100 N	Approved according to DIN EN 61386-23	Yes
Approved according to UR	Yes	Approved according to CSA	No	Material filament	Helix of rigid plastic
Plain interior	Yes	Plain exterior	No	Flexibility	Flexible
Approved according to N	No				

Technical Characteristics

Lunghezza Bobina 30 m

Documentation available for download

Certification

Certificato UL
GUAINE E173313-
2021.pdf

Barcode



8054320282617

Cardboard

30 MT

0.5x0.5x0.13 [m]

4.5 [kg]



8059307210829

Pallet

2400 MT

360 [kg]