

ECGFE25N

FLEXIBLE SPIRAL CONDUIT 23114 Ø25 mm - 30 m - BLACK

Conduits and fittings > Spiral conduits > Flexible spiral conduits > Series gfe - class 23114 - 320 n > Spiral flexible conduits



IMMAGINE RAPPRESENTATIVA EC REPRESENTATIVE IMAGE

Technical Symbols/Marks/Approvals



Norms

EN 61386-1 EN 61386-23 UL 1696

Etim

GROUP EG000003 - Protective hose systems

CLASS EC001177 - Protective plastic hose

Material	Polyvinyl chloride (PVC)	Halogen free	No	Colour	Black
UV resistant	Yes	Working temperature	5-60 °C	Nominal diameter	25 mm
Inner diameter	25 mm	Outer diameter	30.6 mm	Compressive strength	320 N
Bending radius, static	250 mm	Tensile strength	100 N	Approved according to DIN EN 61386-23	Yes
Approved according to UR	Yes	Approved according to CSA	No	Material filament	Helix of rigid plastic
Plain interior	Yes	Plain exterior	No	Flexibility	Flexible
Approved according to N	No				

Technical Characteristics

Lunghezza Bobina 30 m

Documentation available for download

Certification
Certificato UL
GUAINE E173313-
2021.pdf

Certification
Serie Guaine e
raccordi
IMQ_CA02.06109_
2023.pdf

Barcode



8050880888535

Cardboard

30 MT

0.48x0.48x0.18 [m]

5.499 [kg]



8057711593859

Pallet

1950 MT

357.435 [kg]