elettrocanali
THE ITALIAN EVOLUTION OF ELECTRICITY

TECHNICAL DATA SHEET




# ECGFLEX20

## COUPLING FOR PLIABLE CONDUIT IP40 20 mm - TRANSLUCENT

Conduits and fittings > Accessories and fittings > Joints and fittings > Ip40-ip64 fittings > Joint for corrugeted conduits > Joints for corrugated conduits

### Technical Symbols/Marks/Approvals

IP40 | HF | GWT 650° | CE | RoHS II | NF | MADE IN ITALY

### Norms

EN 61386-1 EN 61386-22

## Description

Joint for Halogen-Free polyethylene corrugated pipe. Resistance to abnormal heat (GWT, IEC 60695-2-11 standard): up to 650°C. Protection rating: IP40. Insulation resistance > 100 MΩ. Installation temperature: minimum -5°C, maximum +90°C.
Regulatory references: EN 61386-1, EN 61386-22.
Nominal internal diameter 20 mm

## Etim

### GROUP EG000002 - Pipes/hoses for cable installation

### CLASS EC001492 - Coupler for cable protection tube for underground application

| | | | | | |
|---|---|---|---|---|---|
| **Material** | Plastic | **Material quality** | Polyethylene (PE) | **Halogen free** | Yes |
| **Surface protection** | Untreated | **Colour** | Colourless | **UV resistant** | No |
| **Surface polished** | No | **Separable** | No | **Inner diameter** | 19.8 mm |
| **Outer diameter** | 23.2 mm | **Nominal diameter, connection 1** | 20 mm | **Nominal diameter, connection 2** | 20 mm |
| **Reducing** | No | **With rubber seal** | No | | |

## Technical Characteristics

| | |
|---|---|
| **length** | 55 mm |

**ELETTROCANALI s.p.a.** | Via Gen. C. A. dalla Chiesa, 18 - 24020 Scanzorosciate BG Italy | T. +39 035 665077 | info@elettrocanali.com

Information, dimensions, diagrams and images are provided for informational purposes only and are current as of the date indicated. These elements may be subject to change at any time.

## Documentation available for download



**Certification**

LICENCE - ICTA - 2022 - Licence - Certificat Produits-14693487-778130-0000732967-9.p....pdf

## Barcode

8050880888641

**Pack**

100 NR

0.65 [kg]

8057711593965

**Cardboard**

1200 NR

0.605x0.4x0.26 [m]

7.8 [kg]



Information, dimensions, diagrams and images are provided for informational purposes only and are current as of the date indicated. These elements may be subject to change at any time.