

ECGFLEX25

COUPLING FOR PLIABLE CONDUIT IP40 25 mm - TRANSLUCENT



IMMAGINE RAPPRESENTATIVA  REPRESENTATIVE IMAGE

Conduits and fittings > Accessories and fittings > Joints and fittings > Ip40-ip64 fittings > Joint for corrugated conduits > Joints for corrugated conduits

Technical Symbols/Marks/Approvals



Norms

EN 61386-1 EN 61386-22

Description

Joint for Halogen-Free polyethylene corrugated pipe. Resistance to abnormal heat (GWT, IEC 60695-2-11 standard): up to 650°C. Protection rating: IP40. Insulation resistance > 100 MΩ. Installation temperature: minimum -5°C, maximum +90°C. Regulatory references: EN 61386-1, EN 61386-22. Nominal internal diameter 25 mm

Etim

GROUP EG000002 - Pipes/hoses for cable installation


CLASS EC001492 - Coupler for cable protection tube for underground application

Material	Plastic	Material quality	Polyethylene (PE)	Halogen free	Yes
Surface protection	Untreated	Colour	Colourless	UV resistant	No
Surface polished	No	Separable	No	Inner diameter	23.8 mm
Outer diameter	28.4 mm	Nominal diameter, connection 1	25 mm	Nominal diameter, connection 2	25 mm
Reducing	No	With rubber seal	No		

Technical Characteristics

length 55 mm

Documentation available for download



Certification

LICENCE - ICTA -
2022 - Licence -
Certificat Produits-
14693487-778130-
0000732967-
9.p....pdf

Barcode



8050880888658

Pack

100 NR

1 [kg]



8057711593972

Cardboard

700 NR

0.605x0.4x0.26 [m]

7 [kg]