

ECGFLEX40

COUPLING FOR PLIABLE CONDUIT IP40 40 mm - TRANSLUCENT



IMMAGINE RAPPRESENTATIVA  REPRESENTATIVE IMAGE

Conduits and fittings > Accessories and fittings > Joints and fittings > Ip40-ip64 fittings > Joint for corrugated conduits > Joints for corrugated conduits

Technical Symbols/Marks/Approvals

IP40	HF	GWT 650°	CE	RoHS II	MADE IN ITALY
------	----	-------------	----	---------	---------------------

Norms

EN 61386-1 EN 61386-22

Etim

GROUP EG000002 - Pipes/hoses for cable installation

CLASS EC001492 - Coupler for cable protection tube for underground application

Material	Plastic	Material quality	Polyethylene (PE)	Halogen free	Yes
Surface protection	Untreated	Colour	Colourless	UV resistant	No
Surface polished	No	Separable	No	Inner diameter	38.9 mm
Outer diameter	44 mm	Nominal diameter, connection 1	40 mm	Nominal diameter, connection 2	40 mm
Reducing	No	With rubber seal	No		

Technical Characteristics

length 80 mm

Barcode



8050880888672

Cardboard

300 NR

0.605x0.4x0.26 [m]

6.51 [kg]