

## ECGFLEX40

### COUPLING FOR PLIABLE CONDUIT IP40 40 mm - TRANSLUCENT



IMMAGINE RAPPRESENTATIVA  REPRESENTATIVE IMAGE

Conduits and fittings > Accessories and fittings > Joints and fittings > Ip40-ip64 fittings > Joint for corrugated conduits > Joints for corrugated conduits

#### Technical Symbols/Marks/Approvals

IP40	HF	GWT 650°	CE	RoHS II	MADE IN ITALY
------	----	-------------	----	---------	---------------------

#### Norms

EN 61386-1 EN 61386-22

### Description

Joint for Halogen-Free polyethylene corrugated pipe. Resistance to abnormal heat (GWT, IEC 60695-2-11 standard): up to 650°C. Protection rating: IP40. Insulation resistance > 100 MΩ. Installation temperature: minimum -5°C, maximum +90°C. Regulatory references: EN 61386-1, EN 61386-22. Nominal internal diameter 40 mm

### Etim

**GROUP EG000002 - Pipes/hoses for cable installation**

**CLASS EC001492 - Coupler for cable protection tube for underground application**

<b>Material</b>	Plastic	<b>Material quality</b>	Polyethylene (PE)	<b>Halogen free</b>	Yes
<b>Surface protection</b>	Untreated	<b>Colour</b>	Colourless	<b>UV resistant</b>	No
<b>Surface polished</b>	No	<b>Separable</b>	No	<b>Inner diameter</b>	38.9 mm
<b>Outer diameter</b>	44 mm	<b>Nominal diameter, connection 1</b>	40 mm	<b>Nominal diameter, connection 2</b>	40 mm
<b>Reducing</b>	No	<b>With rubber seal</b>	No		

### Technical Characteristics

length 80 mm

## Barcode



8050880888672

**Cardboard**

300 NR

0.605x0.4x0.26 [m]

6.51 [kg]