

ECGFLEX50

COUPLING FOR PLIABLE CONDUIT IP40 50 mm - TRANSLUCENT



IMMAGINE RAPPRESENTATIVA  REPRESENTATIVE IMAGE

Conduits and fittings > Accessories and fittings > Joints and fittings > Ip40-ip64 fittings > Joint for corrugated conduits > Joints for corrugated conduits

Technical Symbols/Marks/Approvals

IP40	HF	GWT 650°	CE	RoHS II	MADE IN ITALY
------	----	-------------	----	---------	---------------------

Norms

EN 61386-1 EN 61386-22

Description

Joint for Halogen-Free polyethylene corrugated pipe. Resistance to abnormal heat (GWT, IEC 60695-2-11 standard): up to 650°C. Protection rating: IP40. Insulation resistance > 100 MΩ. Installation temperature: minimum -5°C, maximum +90°C. Regulatory references: EN 61386-1, EN 61386-22. Nominal internal diameter 50 mm

Etim

GROUP EG000002 - Pipes/hoses for cable installation

CLASS EC001492 - Coupler for cable protection tube for underground application

Material	Plastic	Material quality	Polyethylene (PE)	Halogen free	Yes
Surface protection	Untreated	Colour	Colourless	UV resistant	No
Surface polished	No	Separable	No	Inner diameter	48.9 mm
Outer diameter	53.5 mm	Nominal diameter, connection 1	50 mm	Nominal diameter, connection 2	50 mm
Reducing	No	With rubber seal	No		

Technical Characteristics

length 90 mm

Barcode



8050880888689

Cardboard

150 NR

0.605x0.4x0.36 [m]

4.8 [kg]