

ECGSU20

LONG JOINT IP40 Ø20 mm - GREY

Conduits and fittings > Accessories and fittings > Joints and fittings > Ip40-ip64 fittings > Joint conduit - conduit > Long rigid conduit joints



Technical Symbols/Marks/Approvals

IP40	UL94 V0	GWT 960°	IK07	CE	RoHS II		
MADE IN ITALY							

Norms

EN 61386-1 EN 61386-21

Description

Coupling for the connection between two pipes of the same diameter, made of shockproof technopolymer based on rigid PVC. IP40 protection degree. V0 self-extinguishing grade according to UL94 standard. Resistance to abnormal heat (GWT IEC 60695-2-11): up to 960 °C. Manufactured in compliance with EN 61386-1 and EN 61386-21 standards. Diameter 20 mm - Length 80 mm

Etim

GROUP EG000002 - Pipes/hoses for cable installation


CLASS EC000939 - Coupler for installation tubes

Material	Plastic	Material quality	Polyvinyl chloride (PVC)	Halogen free	No
Surface protection	Untreated	Colour	Grey	Model	Plug-in
UV resistant	Yes	Quality of surface coating	Uncoated	Surface polished	No
Surface brushed	No	For nominal tube diameter	20 mm	Two-part	No
With inspection opening and cover	No	With lock function	No	Material sealing	No sealing
With outer thread	No	With inner thread	No	Separable	No
Eccentric	No				


Technical Characteristics

length 80 mm

Documentation available for download



Certification
Tubo Rigido TG15
e
Raccordi_2023.pdf




Certification
LICENCE NF -
TG15 -2022 -
Licence - Certificat
Produits-14694838-
778138-
0000732340-
6.p....pdf

Barcode



8050880888832
Pack
100 NR
1.28 [kg]



8057711594108
Cardboard
800 NR
0.605x0.4x0.26 [m]
10.24 [kg]