elettrocanali
THE ITALIAN EVOLUTION OF ELECTRICITY

TECHNICAL DATA SHEET



ECGU10060B

STRAIGHT JOINT DIM.100X60 WHITE

Trunkings > Wall and ceiling > Solid cable trunkings > Series cp - fittings > Joint unit for cable trunkings

Technical Symbols/Marks/Approvals

IP40 | IK07 | GWT 650° | CE | RoHS II | MADE IN ITALY

Norms

EN 50085-1 EN50085-2-1

Description

Linear joint for joining two straight sections of duct. Snap-on connection to the duct. Can also be used to create a "T" joint.

Etim

GROUP EG000006 - Installation ducts for wall and ceiling

CLASS EC000800 - Cover strip for wall duct

Degree of protection (IP)	IP40	**Material**	Plastic	**Material quality**	Acrylonitrile butadiene styrene (ABS)
Halogen free	Yes	**Anti-bacterial treatment**	No	**Surface protection**	Untreated
Colour	White	**Impact strength**	IK07	**Type of fastening**	Snap on
Model	Duct joint cover	**RAL-number**	9001	**Working temperature**	-5 ÷ 60 °C
Shape	Symmetric	**Cover width**	100 mm	**Suitable for wall duct width**	0 mm
Suitable for depth of wall duct	60 mm				

Documentation available for download



Certification

Canali CPH IMQ_CA02.06517_2020.pdf



Certification

Canali e Minic Serie MC-CP.pdf



Certification

LICENCE 669941_CP-MC.pdf

Information, dimensions, diagrams and images are provided for informational purposes only and are current as of the date indicated. These elements may be subject to change at any time.

Barcode

8050880888948

Cardboard

20 NR

0.39x0.295x0.15 [m]

1.7 [kg]

Information, dimensions, diagrams and images are provided for informational purposes only and are current as of the date indicated. These elements may be subject to change at any time.