

ECGX12-11



**IP65 SPIRAL CONDUIT 12-BOX JOINT-
PG THREAD-PG11 - GREY**



Conduits and fittings > Accessories and fittings > Joints and fittings > Series gx - ip65 fittings for spiral conduits > Coupler spiral conduit - box > Pg pitch - grey

Technical Symbols/Marks/Approvals



Norms

EN 61386-1 EN 61386-23 UL 1696

Description

Connector for flexible spiral conduit to junction box, made of shockproof PP-based technopolymer. V2 self-extinguishing grade according to UL94 standard. Resistance to abnormal heat (GWT IEC 60695-2-11): up to 750 °C. Conduit inlet with self-locking thread. Rotating upper part, complete with pre-assembled locknut. Conduit 12 mm - PG11 Thread

Etim

GROUP EG000003 - Protective hose systems

CLASS EC001178 - Screw connection for protective plastic hose

Degree of protection (IP)	IP65	Colour	Grey	Model	Straight
Working temperature	-25-65 °C	Nominal diameter	12 mm	Material sealing	No sealing
Revolving thread	Yes	Construction type	Internal thread	Type of connection	Thread
Thread connection size	PG11	One-piece	Yes	Material screw gland	Polypropylene (PP)
Lowest inner diameter hose	12 mm	Approved in combination with protective conduit according to DIN EN 61386-23	Yes	Approved in combination with protective conduit UR	Yes

Documentation available for download

Certification

Certificato UL
GUAINA E173313-
2021.pdf

Barcode



8050880889273

Pack

25 NR

0.2 [kg]



8057711594412

Cardboard

500 NR

0.305x0.39x0.21 [m]

4 [kg]