

**ECGX12-13**



**IP65 SPIRAL CONDUIT 12-BOX JOINT-  
PG THREAD-PG13,5 - GREY**



Conduits and fittings > Accessories and fittings > Joints and fittings > Series gx - ip65 fittings for spiral conduits > Coupler spiral conduit - box > Pg pitch - grey

**Technical Symbols/Marks/Approvals**

IP65	UL94 V2	GWT 750°	CE	RoHS II	UL US	MADE IN ITALY
------	------------	-------------	----	---------	----------	---------------------

**Norms**

EN 61386-1 EN 61386-23 UL 1696

**Description**

Connector for flexible spiral conduit to junction box, made of shockproof PP-based technopolymer. V2 self-extinguishing grade according to UL94 standard. Resistance to abnormal heat (GWT IEC 60695-2-11): up to 750 °C. Conduit inlet with self-locking thread. Rotating upper part, complete with pre-assembled locknut. Conduit 12 mm - PG13.5 Thread

**Etim**

**GROUP EG000003 - Protective hose systems**

**CLASS EC001178 - Screw connection for protective plastic hose**

<b>Degree of protection (IP)</b>	IP65	<b>Colour</b>	Grey	<b>Model</b>	Straight
<b>Working temperature</b>	-25-65 °C	<b>Nominal diameter</b>	12 mm	<b>Material sealing</b>	No sealing
<b>Revolving thread</b>	Yes	<b>Construction type</b>	Internal thread	<b>Type of connection</b>	Thread
<b>Thread connection size</b>	PG13.5	<b>One-piece</b>	Yes	<b>Material screw gland</b>	Polypropylene (PP)
<b>Lowest inner diameter hose</b>	12 mm	<b>Approved in combination with protective conduit according to DIN EN 61386-23</b>	Yes	<b>Approved in combination with protective conduit UR</b>	Yes

**Documentation available for download**

**Certification**

Certificato UL  
GUAINA E173313-  
2021.pdf

## Barcode



8050880889297

**Pack**

25 NR

0.2 [kg]



8057711594436

**Cardboard**

500 NR

0.305x0.39x0.21 [m]

4 [kg]