

ECGX16M



**IP65 SPIRAL CONDUIT 16-BOX JOINT-
M THREAD-20 mm - GREY**



Conduits and fittings > Accessories and fittings > Joints and fittings > Series gx - ip65 fittings for spiral conduits > Coupler spiral conduit - box > Metric pitch - grey

Technical Symbols/Marks/Approvals



Norms

EN 61386-1 EN 61386-23 UL 1696

Description

Connector for flexible spiral conduit to junction box, made of shockproof PP-based technopolymer. V2 self-extinguishing grade according to UL94 standard. Resistance to abnormal heat (GWT IEC 60695-2-11): up to 750 °C. Conduit inlet with self-locking thread. Rotating upper part, complete with pre-assembled locknut. Conduit 16 mm - 20 mm metric Thread

Etim

GROUP EG000003 - Protective hose systems

CLASS EC001178 - Screw connection for protective plastic hose

Degree of protection (IP)	IP65	Colour	Grey	Model	Straight
Working temperature	-25-65 °C	Nominal diameter	16 mm	Thread length	20 mm
Material sealing	No sealing	Revolving thread	Yes	Construction type	Internal thread
Type of connection	Thread	Thread connection size	M20 x 1.5	One-piece	Yes
Material screw gland	Polypropylene (PP)	Lowest inner diameter hose	16 mm	Approved in combination with protective conduit according to DIN EN 61386-23	Yes
Approved in combination with protective conduit UR	Yes				

Documentation available for download



Certification

Certificato UL
GUAINA E173313-
2021.pdf



Certification

Serie Guaine e
raccordi
IMQ_CA02.06109_
2023.pdf

Barcode



8050880889457

Pack

25 NR

0.3075 [kg]



8057711594597

Cardboard

350 NR

4.305 [kg]