

ECGX20

**IP65 SPIRAL CONDUIT 20-BOX JOINT-GAS THREAD
-3/4" - GREY**

Conduits and fittings > Accessories and fittings > Joints and fittings > Series gx - ip65 fittings for spiral conduits > Coupler spiral conduit - box > Gas pitch - grey



Technical Symbols/Marks/Approvals



Norms

EN 61386-1 EN 61386-23 UL 1696

Description

Connector for flexible spiral conduit to junction box, made of shockproof PP-based technopolymer. V2 self-extinguishing grade according to UL94 standard. Resistance to abnormal heat (GWT IEC 60695-2-11): up to 750 °C. Conduit inlet with self-locking thread. Rotating upper part, complete with pre-assembled locknut. Conduit 20 mm - 3/4" Thread

Etim

GROUP EG000003 - Protective hose systems
CLASS EC001178 - Screw connection for protective plastic hose

| | | | | | |
|-----------------------------------|-----------|---|-------|---|--------------------|
| Degree of protection (IP) | IP65 | Colour | Grey | Model | Straight |
| Working temperature | -25-65 °C | Nominal diameter | 20 mm | Material sealing | No sealing |
| Nominal size in inch | 3/4 inch | Revolving thread | Yes | Construction type | Internal thread |
| Type of connection | Thread | One-piece | Yes | Material screw gland | Polypropylene (PP) |
| Lowest inner diameter hose | 20 mm | Approved in combination with protective conduit according to DIN EN 61386-23 | Yes | Approved in combination with protective conduit UR | Yes |

Documentation available for download

Certification

Certificato UL
GUAINE E173313-
2021.pdf

Barcode



8050880889488

Pack

25 NR

0.45 [kg]



8057711594627

Cardboard

250 NR

4.5 [kg]