

ECGX25-29N

IP65 SPIRAL CONDUIT 25-BOX JOINT-PG THREAD-PG29 - BLACK



Conduits and fittings > Accessories and fittings > Joints and fittings > Series gx - ip65 fittings for spiral conduits > Coupler spiral conduit - box > Pg pitch - black

Technical Symbols/Marks/Approvals



Norms

EN 61386-1 EN 61386-23 UL 1696

Description

Connector for flexible spiral conduit to junction box, made of shockproof PP-based technopolymer. V2 self-extinguishing grade according to UL94 standard. Resistance to abnormal heat (GWT IEC 60695-2-11): up to 750 °C. Conduit inlet with self-locking thread. Rotating upper part, complete with pre-assembled locknut. Conduit 25 mm - PG29 Thread

Etim

GROUP EG000003 - Protective hose systems
CLASS EC001178 - Screw connection for protective plastic hose

Degree of protection (IP)	IP65	Colour	Black	Model	Straight
Working temperature	-25-65 °C	Nominal diameter	25 mm	Material sealing	No sealing
Revolving thread	Yes	Construction type	Internal thread	Type of connection	Thread
Thread connection size	PG29	One-piece	Yes	Material screw gland	Polypropylene (PP)
Lowest inner diameter hose	25 mm	Approved in combination with protective conduit according to DIN EN 61386-23	Yes	Approved in combination with protective conduit UR	Yes

Documentation available for download

Certification

Certificato UL
GUAINE E173313-
2021.pdf

Barcode



8050880889600

Pack

10 NR

0.333 [kg]



8057711594740

Cardboard

150 NR

4.995 [kg]