

ECGX25M

IP65 SPIRAL CONDUIT 25-BOX JOINT-M THREAD-32 mm - GREY

Conduits and fittings > Accessories and fittings > Joints and fittings > Series gx - ip65 fittings for spiral conduits > Coupler spiral conduit - box > Metric pitch - grey



Technical Symbols/Marks/Approvals



Norms

EN 61386-1 EN 61386-23 UL 1696

Description

Connector for flexible spiral conduit to junction box, made of shockproof PP-based technopolymer. V2 self-extinguishing grade according to UL94 standard. Resistance to abnormal heat (GWT IEC 60695-2-11): up to 750 °C. Conduit inlet with self-locking thread. Rotating upper part, complete with pre-assembled locknut. Conduit 25 mm - 32 mm metric Thread

Etim

GROUP EG000003 - Protective hose systems

CLASS EC001178 - Screw connection for protective plastic hose

Degree of protection (IP)	IP65	Colour	Grey	Model	Straight
Working temperature	-25-65 °C	Nominal diameter	25 mm	Thread length	32 mm
Material sealing	No sealing	Revolving thread	Yes	Construction type	Internal thread
Type of connection	Thread	Thread connection size	M32 x 1.5	One-piece	Yes
Material screw gland	Polypropylene (PP)	Lowest inner diameter hose	25 mm	Approved in combination with protective conduit according to DIN EN 61386-23	Yes
Approved in combination with protective conduit UR	Yes				

Documentation available for download



Certification
Certificato UL
GUAINA E173313-
2021.pdf




Certification
Serie Guaine e
raccordi
IMQ_CA02.06109_
2023.pdf

Barcode



8050880889617
Pack
10 NR
0.333 [kg]



8057711594757
Cardboard
150 NR
4.995 [kg]