

## ECGX32M

### IP65 SPIRAL CONDUIT 32-BOX JOINT- M THREAD-40 mm - GREY



IMMAGINE RAPPRESENTATIVA EC REPRESENTATIVE IMAGE

Conduits and fittings > Accessories and fittings > Joints and fittings > Series gx - ip65 fittings for spiral conduits > Coupler spiral conduit - box > Metric pitch - grey

#### Technical Symbols/Marks/Approvals



#### Norms

EN 61386-1 EN 61386-23 UL 1696

## Description

Connector for flexible spiral conduit to junction box, made of shockproof PP-based technopolymer. V2 self-extinguishing grade according to UL94 standard. Resistance to abnormal heat (GWT IEC 60695-2-11): up to 750 °C. Conduit inlet with self-locking thread. Rotating upper part, complete with pre-assembled locknut. Conduit 32 mm - 40 mm metric Thread

## Etim

GROUP EG000003 - Protective hose systems

CLASS EC001178 - Screw connection for protective plastic hose

Degree of protection (IP)	IP65	Colour	Grey	Model	Straight
Working temperature	-25-65 °C	Nominal diameter	32 mm	Thread length	40 mm
Material sealing	No sealing	Revolving thread	Yes	Construction type	Internal thread
Type of connection	Thread	Thread connection size	M40 x 1.5	One-piece	Yes
Material screw gland	Polypropylene (PP)	Lowest inner diameter hose	32 mm	Approved in combination with protective conduit according to DIN EN 61386-23	Yes
Approved in combination with protective conduit UR	Yes				

## Documentation available for download



**Certification**

Certificato UL  
GUAINA E173313-  
2021.pdf



**Certification**

Serie Guaine e  
raccordi  
IMQ\_CA02.06109\_  
2023.pdf

## Barcode



8050880889716

**Pack**

10 NR

0.444 [kg]



8057711594856

**Cardboard**

90 NR

3.996 [kg]