

ECGX40



IP65 SPIRAL CONDUIT 40-BOX JOINT- GAS THREAD -1 AND 1/2" - GREY



Conduits and fittings > Accessories and fittings > Joints and fittings > Series gx - ip65 fittings for spiral conduits > Coupler spiral conduit - box > Gas pitch - grey

Technical Symbols/Marks/Approvals

IP65	UL94 V2	GWT 750°	CE	RoHS II	UL US	MADE IN ITALY
------	---------	----------	----	---------	-------	---------------

Norms

EN 61386-1 EN 61386-23 UL 1696

Description

Connector for flexible spiral conduit to junction box, made of shockproof PP-based technopolymer. V2 self-extinguishing grade according to UL94 standard. Resistance to abnormal heat (GWT IEC 60695-2-11): up to 750 °C. Conduit inlet with self-locking thread. Rotating upper part, complete with pre-assembled locknut. Conduit 40 mm - 1" 1/2 Thread

Etim

GROUP EG000003 - Protective hose systems
CLASS EC001178 - Screw connection for protective plastic hose

Degree of protection (IP)	IP65	Colour	Grey	Model	Straight
Working temperature	-25-65 °C	Nominal diameter	40 mm	Material sealing	No sealing
Nominal size in inch	1 1/2 inch	Revolving thread	Yes	Construction type	Internal thread
Type of connection	Thread	One-piece	Yes	Material screw gland	Polypropylene (PP)
Lowest inner diameter hose	40 mm	Approved in combination with protective conduit according to DIN EN 61386-23	Yes	Approved in combination with protective conduit UR	Yes

Documentation available for download

Certification

Certificato UL
GUAINA E173313-
2021.pdf

Barcode



8050880889785

Pack

10 NR

0.583 [kg]



8057711594924

Cardboard

60 NR

3.498 [kg]