

**ECGX40M**



**IP65 SPIRAL CONDUIT 40-BOX JOINT-  
M THREAD-50 mm - GREY**

Conduits and fittings > Accessories and fittings > Joints and fittings > Series gx - ip65 fittings for spiral conduits > Coupler spiral conduit - box > Metric pitch - grey



**Technical Symbols/Marks/Approvals**

IP65	UL94 V2	GWT 750°	CE	RoHS II			MADE IN ITALY
------	------------	-------------	----	---------	--	--	---------------------

**Norms**

EN 61386-1 EN 61386-23 UL 1696

**Description**

Connector for flexible spiral conduit to junction box, made of shockproof PP-based technopolymer. V2 self-extinguishing grade according to UL94 standard. Resistance to abnormal heat (GWT IEC 60695-2-11): up to 750 °C. Conduit inlet with self-locking thread. Rotating upper part, complete with pre-assembled locknut. Conduit 40 mm - 50 mm metric Thread

**Etim**

**GROUP EG000003 - Protective hose systems**

**CLASS EC001178 - Screw connection for protective plastic hose**

<b>Degree of protection (IP)</b>	IP65	<b>Colour</b>	Grey	<b>Model</b>	Straight
<b>Working temperature</b>	-25-65 °C	<b>Nominal diameter</b>	40 mm	<b>Thread length</b>	50 mm
<b>Material sealing</b>	No sealing	<b>Revolving thread</b>	Yes	<b>Construction type</b>	Internal thread
<b>Type of connection</b>	Thread	<b>Thread connection size</b>	M50 x 1.5	<b>One-piece</b>	Yes
<b>Material screw gland</b>	Polypropylene (PP)	<b>Lowest inner diameter hose</b>	40 mm	<b>Approved in combination with protective conduit according to DIN EN 61386-23</b>	Yes
<b>Approved in combination with protective conduit UR</b>	Yes				

## Documentation available for download



### Certification

Certificato UL  
GUAINA E173313-  
2021.pdf



### Certification

Serie Guaine e  
raccordi  
IMQ\_CA02.06109\_  
2023.pdf

## Barcode



8050880889792

### Pack

10 NR

0.583 [kg]



8057711594931

### Cardboard

60 NR

3.498 [kg]