

ECGX50

IP65 SPIRAL CONDUIT 50-BOX JOINT- GAS THREAD - 2" - GREY



IMMAGINE RAPPRESENTATIVA EC REPRESENTATIVE IMAGE

Conduits and fittings > Accessories and fittings > Joints and fittings > Series gx - ip65 fittings for spiral conduits > Coupler spiral conduit - box > Gas pitch - grey

Technical Symbols/Marks/Approvals



Norms

EN 61386-1 EN 61386-23 UL 1696

Description

Connector for flexible spiral conduit to junction box, made of shockproof PP-based technopolymer. V2 self-extinguishing grade according to UL94 standard. Resistance to abnormal heat (GWT IEC 60695-2-11): up to 750 °C. Conduit inlet with self-locking thread. Rotating upper part, complete with pre-assembled locknut. Conduit 50 mm - 2" Thread

Etim

GROUP EG000003 - Protective hose systems

CLASS EC001178 - Screw connection for protective plastic hose

Degree of protection (IP)	IP65	Colour	Grey	Model	Straight
Working temperature	-25-65 °C	Nominal diameter	50 mm	Material sealing	No sealing
Nominal size in inch	2 inch	Revolving thread	Yes	Construction type	Internal thread
Type of connection	Thread	One-piece	Yes	Material screw gland	Polypropylene (PP)
Lowest inner diameter hose	50 mm	Approved in combination with protective conduit according to DIN EN 61386-23	Yes	Approved in combination with protective conduit UR	Yes

Documentation available for download



Barcode



8050880889822

Pack

10 NR

0.66 [kg]



8057711594962

Cardboard

50 NR

3.3 [kg]