

## ECGX50M

### IP65 SPIRAL CONDUIT 50-BOX JOINT- M THREAD-55 mm - GREY



IMMAGINE RAPPRESENTATIVA EC REPRESENTATIVE IMAGE

Conduits and fittings > Accessories and fittings > Joints and fittings > Series gx - ip65 fittings for spiral conduits > Coupler spiral conduit - box > Metric pitch - grey

#### Technical Symbols/Marks/Approvals



#### Norms

EN 61386-1 EN 61386-23 UL 1696

## Description

Connector for flexible spiral conduit to junction box, made of shockproof PP-based technopolymer. V2 self-extinguishing grade according to UL94 standard. Resistance to abnormal heat (GWT IEC 60695-2-11): up to 750 °C. Conduit inlet with self-locking thread. Rotating upper part, complete with pre-assembled locknut. Conduit 50 mm - 55 mm metric Thread

## Etim

**GROUP EG000003 - Protective hose systems**

**CLASS EC001178 - Screw connection for protective plastic hose**

<b>Degree of protection (IP)</b>	IP65	<b>Colour</b>	Grey	<b>Model</b>	Straight
<b>Working temperature</b>	-25-65 °C	<b>Nominal diameter</b>	50 mm	<b>Thread length</b>	55 mm
<b>Material sealing</b>	No sealing	<b>Revolving thread</b>	Yes	<b>Construction type</b>	Internal thread
<b>Type of connection</b>	Thread	<b>Thread connection size</b>	Other	<b>One-piece</b>	Yes
<b>Material screw gland</b>	Polypropylene (PP)	<b>Lowest inner diameter hose</b>	50 mm	<b>Approved in combination with protective conduit according to DIN EN 61386-23</b>	Yes
<b>Approved in combination with protective conduit UR</b>	Yes				

## Documentation available for download



**Certification**  
Certificato UL  
GUAINA E173313-  
2021.pdf




**Certification**  
Serie Guaine e  
raccordi  
IMQ\_CA02.06109\_  
2023.pdf

## Barcode



8050880889839  
**Pack**  
10 NR  
0.66 [kg]



8057711594979  
**Cardboard**  
50 NR  
3.3 [kg]