


**ECICTA20BL**

**HF ICTA PLIABLE PP CONDUIT 34223  
Ø20 mm - 100 m - BLUE**



Conduits and fittings > Conduits > Corrugated conduits > Series icta - pp - class 34223 - 750 n > plastic conduits > Black

**Technical Symbols/Marks/Approvals**



**Norms**

EN 61386-1 EN 61386-22 EN 61034-2 EN 50642

**Etim**

**GROUP EG000002 - Pipes/hoses for cable installation**

**CLASS EC001174 - Plastic installation tube**

|   |                            |  |                           |  |                          |
|---|----------------------------|--|---------------------------|--|--------------------------|
| <b>Flush-mounted installation</b>                         | Yes                        | <b>Material</b>                                      | Polypropylene (PP)        | <b>Halogen free</b>                      | Yes                      |
| <b>Colour</b>   | Blue                       | <b>RAL-number</b>                                    | 5005                      | <b>UV resistant</b>                      | No                       |
| <b>Suitable for underground installation</b>              | No                         | <b>Operating temperature</b>                         | -5-90 °C                  | <b>Bending strength</b>                  | Pliable, self recovering |
| <b>Compressive strength class according to EN 61386-1</b> | Medium (class 3 / 2 Joule) | <b>Impact strength class according to EN 61386-1</b> | Heavy (class 4 / 6 Joule) | <b>With sleeve</b>                       | No                       |
| <b>Fire retardant version</b>                             | Yes                        | <b>Surface mounting</b>                              | No                        | <b>Suitable for installation on wood</b> | Yes                      |
| <b>Suitable for hollow wall installation</b>              | Yes                        | <b>Suitable for concrete installation</b>            | Yes                       | <b>Machine and systems installation</b>  | No                       |
| <b>Suitable for underfloor installation (screed)</b>      | Yes                        | <b>Suitable for outdoor installation</b>             | No                        | <b>Inner diameter</b>                    | 13.5 mm                  |
| <b>Outer diameter</b>                                     | 20 mm                      | <b>High conducting inner coating</b>                 | Yes                       | <b>With metre indication</b>             | No                       |

**Technical Characteristics**

Lunghezza Bobina 100 m

### Documentation available for download



**Certification**  
Test Report ICTA  
Contenuto alogeni  
MI23-0092109-01.pdf



**Brochure**  
BROCHURE TUBI  
doppie.pdf

### Barcode



8054320280903  
**Cardboard**  
100 MT  
0.51x0.51x0.24 [m]  
6.5 [kg]



8054320281153  
**Pallet**  
5000 MT  
0.8x1.2x2.5 [m]  
325 [kg]