

ECICTA20N

**HF ICTA PLIABLE PP CONDUIT 34223
Ø20 mm - 100 m - BLACK**



Conduits and fittings > Conduits > Corrugated conduits > Series icta - pp - class 34223 - 750 n > plastic conduits > Black

Technical Symbols/Marks/Approvals



Norms

EN 61386-1 EN 61386-22 EN 61034-2 EN 50642

Etim

GROUP EG000002 - Pipes/hoses for cable installation

CLASS EC001174 - Plastic installation tube

Flush-mounted installation	Yes	Material	Polypropylene (PP)	Halogen free	Yes
Colour	Black	RAL-number	9005	UV resistant	No
Suitable for underground installation	No	Operating temperature	-5-90 °C	Bending strength	Pliable, self recovering
Compressive strength class according to EN 61386-1	Medium (class 3 / 2 Joule)	Impact strength class according to EN 61386-1	Heavy (class 4 / 6 Joule)	With sleeve	No
Fire retardant version	Yes	Surface mounting	No	Suitable for installation on wood	Yes
Suitable for hollow wall installation	Yes	Suitable for concrete installation	Yes	Machine and systems installation	No
Suitable for underfloor installation (screed)	Yes	Suitable for outdoor installation	No	Inner diameter	13.5 mm
Outer diameter	20 mm	High conducting inner coating	Yes	With metre indication	No

Technical Characteristics

Lunghezza Bobina 100 m

Documentation available for download




Certification
Test Report ICTA
Contenuto alogeni
MI23-0092109-01.pdf



Brochure
BROCHURE TUBI
doppie.pdf

Barcode



8054320280927
Cardboard
100 MT
0.51x0.51x0.24 [m]
6.5 [kg]



8054320281177
Pallet
5000 MT
0.8x1.2x2.5 [m]
325 [kg]