

**ECICTA25VE**

**HF ICTA PLIABLE PP CONDUIT 34223  
Ø25 mm - 100 m - GREEN**



IMMAGINE RAPPRESENTATIVA EC REPRESENTATIVE IMAGE

Conduits and fittings > Conduits > Corrugated conduits > Series icta - pp - class 34223 - 750 n > plastic conduits > Black

**Technical Symbols/Marks/Approvals**

HF	GWT 850°	+90°		CE	RoHS II	MADE IN ITALY
----	----------	------	--	----	---------	---------------

**Norms**

EN 61386-1 EN 61386-22 EN 61034-2 EN 50642

**Etim**

**GROUP EG000002 - Pipes/hoses for cable installation**

**CLASS EC001174 - Plastic installation tube**

<b>Flush-mounted installation</b>	Yes	<b>Material</b>	Polypropylene (PP)	<b>Halogen free</b>	Yes
<b>Colour</b>	Green	<b>RAL-number</b>	6029	<b>UV resistant</b>	No
<b>Suitable for underground installation</b>	No	<b>Operating temperature</b>	-5-90 °C	<b>Bending strength</b>	Pliable, self recovering
<b>Compressive strength class according to EN 61386-1</b>	Medium (class 3 / 2 Joule)	<b>Impact strength class according to EN 61386-1</b>	Heavy (class 4 / 6 Joule)	<b>With sleeve</b>	No
<b>Fire retardant version</b>	Yes	<b>Surface mounting</b>	No	<b>Suitable for installation on wood</b>	Yes
<b>Suitable for hollow wall installation</b>	Yes	<b>Suitable for concrete installation</b>	Yes	<b>Machine and systems installation</b>	No
<b>Suitable for underfloor installation (screed)</b>	Yes	<b>Suitable for outdoor installation</b>	No	<b>Inner diameter</b>	18.4 mm
<b>Outer diameter</b>	25 mm	<b>High conducting inner coating</b>	Yes	<b>With metre indication</b>	No

**Technical Characteristics**

Lunghezza Bobina 100 m

## Documentation available for download




**Certification**  
Test Report ICTA  
Contenuto alogeni  
MI23-0092109-  
01.pdf



**Brochure**  
BROCHURE TUBI  
doppie.pdf

## Barcode



8054320280880  
**Cardboard**  
100 MT  
0.62x0.62x0.27 [m]  
8.82 [kg]



8054320281139  
**Pallet**  
3600 MT  
0.8x1.2x2.5 [m]  
317.52 [kg]