

ECICTA32

**HF ICTA PLIABLE PP CONDUIT 34223
Ø32 mm - 50 m - GREY**



IMMAGINE RAPPRESENTATIVA EC REPRESENTATIVE IMAGE

Conduits and fittings > Conduits > Corrugated conduits > Series icta - pp - class 34223 - 750 n > plastic conduits > Grey

Technical Symbols/Marks/Approvals

HF	GWT 850°	+90°		CE	RoHS II	NF	MADE IN ITALY
-----------	-----------------	-------------	--	-----------	----------------	-----------	----------------------

Norms

EN 61386-1 EN 61386-2 EN 61034-2 EN 50642

Etim

GROUP EG000002 - Pipes/hoses for cable installation

CLASS EC001174 - Plastic installation tube

Flush-mounted installation	Yes	Material	Polypropylene (PP)	Halogen free	Yes
Colour	Grey	RAL-number	7037	UV resistant	No
Suitable for underground installation	No	Operating temperature	-5-90 °C	Bending strength	Pliable, self recovering
Compressive strength class according to EN 61386-1	Medium (class 3 / 2 Joule)	Impact strength class according to EN 61386-1	Heavy (class 4 / 6 Joule)	With sleeve	No
Fire retardant version	Yes	Surface mounting	No	Suitable for installation on wood	Yes
Suitable for hollow wall installation	Yes	Suitable for concrete installation	Yes	Machine and systems installation	No
Suitable for underfloor installation (screed)	Yes	Suitable for outdoor installation	No	Inner diameter	24.4 mm
Outer diameter	32 mm	High conducting inner coating	Yes	With metre indication	No

Documentation available for download

Certification

LICENCE - ICTA - 2022 - Licence - Certificat Produits-14693487-778130-0000732967-9.p....pdf

Certification

Test Report ICTA Contenuto alogeni MI23-0092109-01.pdf

Brochure

BROCHURE TUBI doppie.pdf

Barcode



8050880889983

Cardboard

50 MT

0.55x0.55x0.27 [m]

6.415 [kg]



8057711595129

Pallet

1800 MT

0.8x1.2x2.5 [m]

230.94 [kg]