

ECICTA32TVE

HF ICTA PLIABLE PP CONDUIT 34223 Ø32 mm - 50 m WITH DRAW TAPE - GREEN

Technical Symbols/Marks/Approvals



Norms

- EN 61386-1 EN 61386-22 IEC 60754-1 IEC 60754-2 EN 61034-2
- EN 50642

Etim

GROUP EG000002 - Pipes/hoses for cable installation

CLASS EC001174 - Plastic installation tube

Flush-mounted installation	Yes	Material	Polypropylene (PP)	Halogen free	Yes
Colour	Green	RAL-number	6029	UV resistant	No
Suitable for underground installation	No	Operating temperature	-5-90 °C	Bending strength	Pliable, self recovering
Compressive strength class according to EN 61386-1	Medium (class 3 / 2 Joule)	Impact strength class according to EN 61386-1	Heavy (class 4 / 6 Joule)	With sleeve	No
Fire retardant version	Yes	Surface mounting	No	Suitable for installation on wood	Yes
Suitable for hollow wall installation	Yes	Suitable for concrete installation	Yes	Machine and systems installation	No
Suitable for underfloor installation (screed)	Yes	Suitable for outdoor installation	No	Inner diameter	24.4 mm
Outer diameter	32 mm	High conducting inner coating	Yes	With metre indication	No

Documentation available for download

Certification

Test Report ICTA
Contenuto alogeni
MI23-0092109-01.pdf

Barcode



8059307211963

Cardboard

50 MT

0.55x0.55x0.27 [m]

6.615 [kg]



8059307211789

Pallet

1800 MT

0.8x1.2x2.5 [m]

238.14 [kg]