



ECK11100N

MULTIPLE SOCKET COM. BLACK 3 GANGS



Residential > Utility series > Items for domestic use > Multiple socket bases > Multiple sockets > Straight multiple socket base with cable



Technical Symbols/Marks/Approvals

Norms

CEI 23-50 CEI 23-124



Etim

GROUP EG000013 - Domestic switching devices

CLASS EC000330 - Socket outlet combination

Degree of protection (IP)	IP20	RAL-number (similar)	9005	Material	Plastic
Material quality	Thermoplastic	Halogen free	No	Anti-bacterial treatment	No
Surface protection	Untreated	Surface finishing	Glossy	Colour	Black
Transparent	No	Impact strength	IK09	Working temperature	-15-35 °C
Compatible with Apple Homek	(it No	Compatible with Google Assistant	No	Compatible with Amazon Alexa	No
IFTTT support available	No	Overvoltage protection	No	With miniature fuse	No
With on/off switch	Yes	Rotated central insert	No	Nominal current	16 A
Core cross section	1 mm²	Number of socket outlets with protective contact CEE 7/3 (type F)	2	Number of socket outlets British Standard BS 1363	0
Number of socket outlets Italia standard type Bipasso	an 6	Number of socket outlets Italian standard type P11	0	Number of socket outlets Italian standard type P17	0
Number of socket outlets Italia standard type P30	an 0	Number of universal multi standard sockets	0	Number of socket outlets Swiss standard type 13	0
Number of socket outlets Swis standard type 15	os 0	Number of socket outlets Swiss standard type 23	0	Number of socket outlets Swiss standard type 25	0
Type of mains connection	Italian type P17	NEMA designation	None	Housing shape	Rectangular
Number of socket outlets CEE 7/1 (no protective contact)	0	Number of socket outlets CEE 7/16 (EURO)	0	Number of socket outlets with earth pin	6
Number of cold device socket outlets	0	Number of socket outlets Danish standard (earthing pin, type K)	0	Number of socket outlets with protective contact CEE 7/5 (type E)	0
Number of NEMA-outlets	0	Residual current circuit breaker (RCCB)	No	Mains filter	No
Number of other socket outlet	s 0	Number of USB connections	0	Overcurrent protection	No
Max. connected load	3500 W	With cover	No	Length of power cord	1.5 m
Type of plug	Straight	Directly pluggable (without power cord)	No		

Barcode



8053676577903

Unit 1 NR

0.325 [kg]



8059307219525

Cardboard

40 NR

0.205x0.395x0.445 [m]

13 [kg]