

## ECK11104



### MULTIPLE SOCKET WHITE 4 GANGS

Residential > Utility series > Items for domestic use > Multiple socket bases > Multiple sockets > 45° multiple socket base with cable



#### Technical Symbols/Marks/Approvals



#### Norms

CEI 23-50 CEI 23-124

### Description

Schuko/dual-standard power strip with 45° angled sockets, including cable, plug, and illuminated switch. 4 Schuko/dual-standard sockets 2P+E 10/16A type P17/11-30. Made of self-extinguishing V0 technopolymer (UL94 Standard) with high UV resistance. White color. Sockets protected against accidental contact. 2P+E 16A plug type S17 molded to the cable with protected nickel-plated brass pins. H05VV-F 3G1 cable - double insulation - VDE - length 1.5 m. Rated voltage: 250 V~. Maximum power: 3,500 W. Abnormal heat resistance (GWT, IEC 60695-2-11 standard): up to 750°C. Protection rating: IP20. Operating temperature: -15°C to +35°C.

## Etim

### GROUP EG000013 - Domestic switching devices

### CLASS EC000330 - Socket outlet combination

|   |                   |  |        |  |             |
|---|-------------------|--|--------|--|-------------|
| <b>Degree of protection (IP)</b>                                | IP20              | <b>RAL-number (similar)</b>  | 9003   | <b>Material</b>  | Plastic     |
| <b>Material quality</b>   | Thermoplastic     | <b>Halogen free</b>  | No     | <b>Anti-bacterial treatment</b>  | No          |
| <b>Surface protection</b>                                       | Untreated         | <b>Surface finishing</b>   | Glossy | <b>Colour</b>  | White       |
| <b>Transparent</b>  | No                | <b>Impact strength</b>   | IK09   | <b>Working temperature</b>   | -15-35 °C   |
| <b>Compatible with Apple HomeKit</b>                            | No                | <b>Compatible with Google Assistant</b>                                  | No     | <b>Compatible with Amazon Alexa</b>                                      | No          |
| <b>IFTTT support available</b>                                  | No                | <b>Overvoltage protection</b>  | No     | <b>With miniature fuse</b>   | No          |
| <b>With on/off switch</b>                                       | Yes               | <b>Rotated central insert</b>  | Yes    | <b>Nominal current</b>   | 16 A        |
| <b>Core cross section</b>                                       | 1 mm <sup>2</sup> | <b>Number of socket outlets with protective contact CEE 7/3 (type F)</b> | 4      | <b>Number of socket outlets British Standard BS 1363</b>                 | 0           |
| <b>Number of socket outlets Italian standard type Bipasso</b>   | 4                 | <b>Number of socket outlets Italian standard type P11</b>                | 0      | <b>Number of socket outlets Italian standard type P17</b>                | 0           |
| <b>Number of socket outlets Italian standard type P30</b>       | 0                 | <b>Number of universal multi standard sockets</b>                        | 0      | <b>Number of socket outlets Swiss standard type 13</b>                   | 0           |
| <b>Number of socket outlets Swiss standard type 15</b>          | 0                 | <b>Number of socket outlets Swiss standard type 23</b>                   | 0      | <b>Number of socket outlets Swiss standard type 25</b>                   | 0           |
| <b>Type of mains connection</b>                                 | Italian type P17  | <b>NEMA designation</b>  | None   | <b>Housing shape</b>   | Rectangular |
| <b>Number of socket outlets CEE 7/1 (no protective contact)</b> | 0                 | <b>Number of socket outlets CEE 7/16 (EURO)</b>                          | 0      | <b>Number of socket outlets with earth pin</b>                           | 4           |
| <b>Number of cold device socket outlets</b>                     | 0                 | <b>Number of socket outlets Danish standard (earthing pin, type K)</b>   | 0      | <b>Number of socket outlets with protective contact CEE 7/5 (type E)</b> | 0           |
| <b>Number of NEMA-outlets</b>                                   | 0                 | <b>Residual current circuit breaker (RCCB)</b>                           | No     | <b>Mains filter</b>  | No          |
| <b>Number of other socket outlets</b>                           | 0                 | <b>Number of USB connections</b>   | 0      | <b>Overcurrent protection</b>  | No          |
| <b>Max. connected load</b>                                      | 3500 W            | <b>With cover</b>  | No     | <b>Length of power cord</b>  | 1.5 m       |
| <b>Type of plug</b>   | Straight          | <b>Directly pluggable (without power cord)</b>                           | No     | <b>Angle rotated central insert</b>                                      | 45°         |

## Barcode



8033576775029

**Unit**

1 NR

0.37 [kg]



8059307219587

**Cardboard**

40 NR

0.295x0.425x0.4 [m]

14.8 [kg]