

ECK11104N

MULTIPLE SOCKET 4 GANGS 10/16A BLACK

Residential > Utility series > Items for domestic use > Multiple socket bases > Multiple sockets > 45° multiple socket base with cable

Technical Symbols/Marks/Approvals

IP20 | UL94 V0 | GWT 750° | CE | RoHS II | MADE IN PRC

Norms

CEI 23-50 CEI 23-124

Description

Schuko/dual-standard power strip with 45° angled sockets, including cable, plug, and illuminated switch. 4 Schuko/dual-standard sockets 2P+E 10/16A type P17/11-30. Made of self-extinguishing V0 technopolymer (UL94 Standard) with high UV resistance. Black color. Sockets protected against accidental contact. 2P+E 16A plug type S17 molded to the cable with protected nickel-plated brass pins. H05VV-F 3G1 cable - double insulation - VDE - length 1.5 m. Rated voltage: 250 V~. Maximum power: 3,500 W. Abnormal heat resistance (GWT, IEC 60695-2-11 standard): up to 750°C. Protection rating: IP20. Operating temperature: -15°C to +35°C.

Information, dimensions, diagrams and images are provided for informational purposes only and are current as of the date indicated. These elements may be subject to change at any time.

Etim

GROUP EG000013 - Domestic switching devices

CLASS EC000330 - Socket outlet combination

Degree of protection (IP)	IP20	**RAL-number (similar)**	9005	**Material**	Plastic
Material quality	Thermoplastic	**Halogen free**	No	**Anti-bacterial treatment**	No
Surface protection	Untreated	**Surface finishing**	Glossy	**Colour**	Black
Transparent	No	**Impact strength**	IK09	**Working temperature**	-15 ÷ 35 °C
Compatible with Apple HomeKit	No	**Compatible with Google Assistant**	No	**Compatible with Amazon Alexa**	No
IFTTT support available	No	**Overvoltage protection**	No	**With miniature fuse**	No
With on/off switch	Yes	**Rotated central insert**	Yes	**Nominal current**	16 A
Core cross section	1 mm²	**Number of socket outlets with protective contact CEE 7/3 (type F)**	4	**Number of socket outlets British Standard BS 1363**	0
Number of socket outlets Italian standard type Bipasso	4	**Number of socket outlets Italian standard type P11**	0	**Number of socket outlets Italian standard type P17**	0
Number of socket outlets Italian standard type P30	0	**Number of universal multi standard sockets**	0	**Number of socket outlets Swiss standard type 13**	0
Number of socket outlets Swiss standard type 15	0	**Number of socket outlets Swiss standard type 23**	0	**Number of socket outlets Swiss standard type 25**	0
Type of mains connection	Italian type P17	**NEMA designation**	None	**Housing shape**	Rectangular
Number of socket outlets CEE 7/1 (no protective contact)	0	**Number of socket outlets CEE 7/16 (EURO)**	0	**Number of socket outlets with earth pin**	4
Number of cold device socket outlets	0	**Number of socket outlets Danish standard (earthing pin, type K)**	0	**Number of socket outlets with protective contact CEE 7/5 (type E)**	0
Number of NEMA-outlets	0	**Residual current circuit breaker (RCCB)**	No	**Mains filter**	No
Number of other socket outlets	0	**Number of USB connections**	0	**Overcurrent protection**	No
Max. connected load	3500 W	**With cover**	No	**Length of power cord**	1.5 m
Type of plug	Straight	**Directly pluggable (without power cord)**	No	**Angle rotated central insert**	45°

Barcode

8053676570232

Unit

1 NR

0.37 [kg]

8059307219594

Cardboard

40 NR

0.4x0.44x0.29 [m]

14.8 [kg]

Information, dimensions, diagrams and images are provided for informational purposes only and are current as of the date indicated. These elements may be subject to change at any time.