

## ECK11106N

### MULTIPLE SOCKET 6 GANGS 10/16A BLACK



IMMAGINE  
RAPPRESENTATIVA



REPRESENTATIVE  
IMAGE

Residential > Utility series > Items for domestic use > Multiple socket bases > Multiple sockets > 45° multiple socket base with cable

#### Technical Symbols/Marks/Approvals



#### Norms

CEI 23-50 CEI 23-124

## Description

Schuko/dual-standard power strip with 45° angled sockets, including cable, plug, and illuminated switch. 6 Schuko/dual-standard sockets 2P+E 10/16A type P17/11-30. Made of self-extinguishing V0 technopolymer (UL94 Standard) with high UV resistance. Black color. Sockets protected against accidental contact. 2P+E 16A plug type S17 molded to the cable with protected nickel-plated brass pins. H05VV-F 3G1 cable - double insulation - VDE - length 1.5 m. Rated voltage: 250 V~. Maximum power: 3,500 W. Abnormal heat resistance (GWT, IEC 60695-2-11 standard): up to 750°C. Protection rating: IP20. Operating temperature: -15°C to +35°C.

## Etim

### GROUP EG000013 - Domestic switching devices

### CLASS EC000330 - Socket outlet combination

<b>Degree of protection (IP)</b>	IP20	<b>RAL-number (similar)</b>	9005	<b>Material</b>	Plastic
<b>Material quality</b>	Thermoplastic	<b>Halogen free</b>	No	<b>Anti-bacterial treatment</b>	No
<b>Surface protection</b>	Untreated	<b>Surface finishing</b>	Glossy	<b>Colour</b>	Black
<b>Transparent</b>	No	<b>Impact strength</b>	IK09	<b>Working temperature</b>	-15-35 °C
<b>Compatible with Apple HomeKit</b>	No	<b>Compatible with Google Assistant</b>	No	<b>Compatible with Amazon Alexa</b>	No
<b>IFTTT support available</b>	No	<b>Overvoltage protection</b>	No	<b>With miniature fuse</b>	No
<b>With on/off switch</b>	Yes	<b>Rotated central insert</b>	Yes	<b>Nominal current</b>	16 A
<b>Core cross section</b>	1 mm <sup>2</sup>	<b>Number of socket outlets with protective contact CEE 7/3 (type F)</b>	6	<b>Number of socket outlets British Standard BS 1363</b>	0
<b>Number of socket outlets Italian standard type Bipasso</b>	6	<b>Number of socket outlets Italian standard type P11</b>	0	<b>Number of socket outlets Italian standard type P17</b>	0
<b>Number of socket outlets Italian standard type P30</b>	0	<b>Number of universal multi standard sockets</b>	0	<b>Number of socket outlets Swiss standard type 13</b>	0
<b>Number of socket outlets Swiss standard type 15</b>	0	<b>Number of socket outlets Swiss standard type 23</b>	0	<b>Number of socket outlets Swiss standard type 25</b>	0
<b>Type of mains connection</b>	Italian type P17	<b>NEMA designation</b>	None	<b>Housing shape</b>	Rectangular
<b>Number of socket outlets CEE 7/1 (no protective contact)</b>	0	<b>Number of socket outlets CEE 7/16 (EURO)</b>	0	<b>Number of socket outlets with earth pin</b>	6
<b>Number of cold device socket outlets</b>	0	<b>Number of socket outlets Danish standard (earthing pin, type K)</b>	0	<b>Number of socket outlets with protective contact CEE 7/5 (type E)</b>	0
<b>Number of NEMA-outlets</b>	0	<b>Residual current circuit breaker (RCCB)</b>	No	<b>Mains filter</b>	No
<b>Number of other socket outlets</b>	0	<b>Number of USB connections</b>	0	<b>Overcurrent protection</b>	No
<b>Max. connected load</b>	3500 W	<b>With cover</b>	No	<b>Length of power cord</b>	1.5 m
<b>Type of plug</b>	Straight	<b>Directly pluggable (without power cord)</b>	No	<b>Angle rotated central insert</b>	45°

## Barcode



8053676570249

**Unit**

1 NR

0.45 [kg]



8059307219624

**Cardboard**

30 NR

0.375x0.43x0.305 [m]

13.5 [kg]