

ECK11107



MULTIPLE SOCKET WHITE 7 GANGS

Residential > Utility series > Items for domestic use > Multiple socket bases > Multiple sockets > 45° multiple socket base with cable



Technical Symbols/Marks/Approvals



Norms

CEI 23-50 CEI 23-124

Description

Schuko/dual-standard power strip with 45° angled sockets, including cable, plug, and illuminated switch. 7 Schuko/dual-standard sockets 2P+E 10/16A type P17/11-30. Made of self-extinguishing V0 technopolymer (UL94 Standard) with high UV resistance. White color. Sockets protected against accidental contact. 2P+E 16A plug type S17 molded to the cable with protected nickel-plated brass pins. H05VV-F 3G1 cable - double insulation - VDE - length 1.5 m. Rated voltage: 250 V~. Maximum power: 3,500 W. Abnormal heat resistance (GWT, IEC 60695-2-11 standard): up to 750°C. Protection rating: IP20. Operating temperature: -15°C to +35°C.

Etim

GROUP EG000013 - Domestic switching devices

CLASS EC000330 - Socket outlet combination

| | | | | | |
|---|-------------------|--|--------|--|-------------|
| Degree of protection (IP) | IP20 | RAL-number (similar) | 9003 | Material | Plastic |
| Material quality | Thermoplastic | Halogen free | No | Anti-bacterial treatment | No |
| Surface protection | Untreated | Surface finishing | Glossy | Colour | White |
| Transparent | No | Impact strength | IK09 | Working temperature | -15-35 °C |
| Compatible with Apple HomeKit | No | Compatible with Google Assistant | No | Compatible with Amazon Alexa | No |
| IFTTT support available | No | Overvoltage protection | No | With miniature fuse | No |
| With on/off switch | Yes | Rotated central insert | Yes | Nominal current | 16 A |
| Core cross section | 1 mm ² | Number of socket outlets with protective contact CEE 7/3 (type F) | 7 | Number of socket outlets British Standard BS 1363 | 0 |
| Number of socket outlets Italian standard type Bipasso | 7 | Number of socket outlets Italian standard type P11 | 0 | Number of socket outlets Italian standard type P17 | 0 |
| Number of socket outlets Italian standard type P30 | 0 | Number of universal multi standard sockets | 0 | Number of socket outlets Swiss standard type 13 | 0 |
| Number of socket outlets Swiss standard type 15 | 0 | Number of socket outlets Swiss standard type 23 | 0 | Number of socket outlets Swiss standard type 25 | 0 |
| Type of mains connection | Italian type P17 | NEMA designation | None | Housing shape | Rectangular |
| Number of socket outlets CEE 7/1 (no protective contact) | 0 | Number of socket outlets CEE 7/16 (EURO) | 0 | Number of socket outlets with earth pin | 7 |
| Number of cold device socket outlets | 0 | Number of socket outlets Danish standard (earthing pin, type K) | 0 | Number of socket outlets with protective contact CEE 7/5 (type E) | 0 |
| Number of NEMA-outlets | 0 | Residual current circuit breaker (RCCB) | No | Mains filter | No |
| Number of other socket outlets | 0 | Number of USB connections | 0 | Overcurrent protection | No |
| Max. connected load | 3500 W | With cover | No | Length of power cord | 1.5 m |
| Type of plug | Straight | Directly pluggable (without power cord) | No | Angle rotated central insert | 45° |

Barcode



8033576775050
Unit
1 NR
0.4767 [kg]



8059307219631
Cardboard
30 NR
0.42x0.42x0.295 [m]
14.301 [kg]