



**ECK11120**

**ADAPTOR TURNABLE PLUG WITH  
LUMINOUS SWITCH**



Residential > Utility series > Items for domestic use > Adaptors > Socket outlet combination > Triple adaptor 16 a - with light switch

**Technical Symbols/Marks/Approvals**



**Norms**

CEI 23-50 CEI 23-151

## Etim

### GROUP EG000013 - Domestic switching devices

#### CLASS EC000330 - Socket outlet combination

Degree of protection (IP)	IP20	RAL-number (similar)	9003	Material	Plastic
Material quality	Thermoplastic	Halogen free	No	Anti-bacterial treatment	No
Surface protection	Untreated	Surface finishing	Glossy	Colour	White
Transparent	No	Impact strength	IK09	Working temperature	-15-35 °C
Compatible with Apple HomeKit	No	Compatible with Google Assistant	No	Compatible with Amazon Alexa	No
IFTTT support available	No	Overvoltage protection	No	With miniature fuse	No
With on/off switch	Yes	Rotated central insert	No	Nominal current	16 A
Number of socket outlets with protective contact CEE 7/3 (type F)	1	Number of socket outlets British Standard BS 1363	0	Number of socket outlets Italian standard type Bipasso	3
Number of socket outlets Italian standard type P11	0	Number of socket outlets Italian standard type P17	0	Number of socket outlets Italian standard type P30	0
Number of universal multi standard sockets	0	Number of socket outlets Swiss standard type 13	0	Number of socket outlets Swiss standard type 15	0
Number of socket outlets Swiss standard type 23	0	Number of socket outlets Swiss standard type 25	0	Type of mains connection	Italian type P17
NEMA designation	None	Housing shape	Rectangular	Number of socket outlets CEE 7/1 (no protective contact)	0
Number of socket outlets CEE 7/16 (EURO)	0	Number of socket outlets with earth pin	3	Number of cold device socket outlets	0
Number of socket outlets Danish standard (earthing pin, type K)	3	Number of socket outlets with protective contact CEE 7/5 (type E)	0	Number of NEMA-outlets	0
Residual current circuit breaker (RCCB)	No	Mains filter	No	Number of other socket outlets	0
Number of USB connections	0	Overcurrent protection	No	Max. connected load	3500 W
With cover	No	Type of plug	Straight	Directly pluggable (without power cord)	Yes

## Barcode



8033954877758

Unit

1 NR

0.1292 [kg]



8057711595242

Pack

12 NR

0.14x0.445x0.135 [m]

1.5504 [kg]



8032793871118

Cardboard

48 NR

0.305x0.47x0.295 [m]

6.2016 [kg]